RAFI

LED T 4.5 superbright, red, 24 V

1.90.690.331/0000



Electrical characteristics of LED Max. current, I _F 13 mA LED wavelength typ. 630 Forward voltage typ. U _F at I _F 24 LED breakdown voltage U _R bei I _F 24 Light intensity 90 Other specifications T 4.5 Color red		
13 mA LED wavelength typ. 630 Forward voltage typ. U _F at I _F 24 LED breakdown voltage U _R bei I _F 24 Light intensity 90 Other specifications T 4.5 Color red	Electrical characteristics of LED	
LED wavelength typ. 630 Forward voltage typ. U _F at I _F 24 LED breakdown voltage U _R bei I _F 24 Light intensity 90 Other specifications 5000000000000000000000000000000000000	Max. current, I _F	
Forward voltage typ. U _F at I _F 24 LED breakdown voltage U _R bei I _F 24 Light intensity 90 Other specifications 5000000000000000000000000000000000000		13 mA
24 LED breakdown voltage U _R bei I _F 24 Light intensity 90 Other specifications Socket T 4.5 Color red	LED wavelength typ.	630
LED breakdown voltage U _R bei I _F 24 Light intensity 90 Other specifications 5000000000000000000000000000000000000	Forward voltage typ. U _F at I _F	
24 Light intensity 90 Other specifications Socket T 4.5 Color red		24
Light intensity 90 Other specifications T 4.5 Color red	LED breakdown voltage U _R bei I _F	
Other specifications Socket T 4.5 Color red		24
Socket T 4.5 Color red	Light intensity	90
Color red	Other specifications	
	Socket	Т 4.5
	Color	red
Ambient temp. operating min30 °C	Ambient temp. operating min.	-30 °C
Ambient temp. operating max. +65 °C	Ambient temp. operating max.	<u>+65 °C</u>
ROHS compliant yes	ROHS compliant	yes
REACH compliant yes	REACH compliant	yes