

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 3, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: black. Connections internally jumpered

#### Your advantages

- ✓ Well-known connection principle allows worldwide use
- Allows connection of two conductors
- Internal bridging for easily looping through potentials
- ☑ Integrated protective guide prevents incorrect insertion of the conductor underneath the tension sleeve
- The latching on the side enables various numbers of positions to be combined



## **Key Commercial Data**

Packing unit	50 pc
GTIN	4 017918 116811
GTIN	4017918116811

#### Technical data

#### Item properties

Brief article description	PCB terminal block
Range of articles	MKDS 3/B
Pitch	5.08 mm
Number of positions	3
Connection method	Screw connection with tension sleeve
Drive form screw head	Slotted (L)
Screw thread	M3
Mounting type	Wave soldering
Pin layout	Linear pinning
Number of levels	1



### Technical data

### Electrical parameters

Rated current	24 A
Rated insulation voltage (III/2)	400 V
Rated surge voltage (III/2)	4 kV

#### Connection capacity

Conductor cross section solid	0.2 mm² 4 mm²
Conductor cross section flexible	0.2 mm² 2.5 mm²
Conductor cross section AWG / kcmil	24 12
Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm² 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.25 mm² 2.5 mm²
2 conductors with same cross section, solid	0.2 mm² 1.5 mm²
2 conductors with same cross section, flexible	0.2 mm² 1.5 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve	0.25 mm² 0.75 mm²
2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve	0.5 mm² 1.5 mm²
Stripping length	8 mm
Torque	0.5 Nm 0.6 Nm

#### Material data - contact

Note	WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/ JEDEC JESD 201
Contact material	Cu alloy
Surface characteristics	Tin-plated
Metal surface terminal point (top layer)	Tin (5 - 7 μm Sn)
Metal surface terminal point (middle layer)	Nickel (2 - 3 µm Ni)
Metal surface soldering area (top layer)	Tin (5 - 7 µm Sn)
Metal surface soldering area (middle layer)	Nickel (2 - 3 µm Ni)

### Material data - housing

Insulating material	PA
Insulating material group	I
CTI according to IEC 60112	600
Flammability rating according to UL 94	V0
Glow wire flammability index GWFI according to EN 60695-2-12	850
Glow wire ignition temperature GWIT according to EN 60695-2-13	775
Temperature for the ball pressure test according to EN 60695-10-2	125 °C

### Dimensions for the product

Caption	Schematic representation – for additional information, see product range drawing in the Download Center
Length [1]	11.2 mm
Width [w]	15.24 mm
Height [ h ]	23 mm



#### Technical data

#### Dimensions for the product

Pitch	5.08 mm
Height (without solder pin)	18 mm
Solder pin [P]	5 mm
Pin dimensions	0.9 x 0.9 mm
Dimension a	10.16 mm

#### Dimensions for PCB design

Hole diameter	1.3 mm
---------------	--------

#### Packaging information

Type of packaging	packed in cardboard
Pieces per package	50
Denomination packing units	Pcs.

#### General product information

Type of note	Note on application
Note	For safe conductor connection, always adhere to a defined tightening torque. Particularly in the case of PCB terminal blocks with two or three positions, the individual solder pin for each contact point cannot compensate for this. That is why the terminal blocks must be supported during conductor connection (held with one hand, support on the housing).

#### Electrical tests

Rated current	24 A
Rated insulation voltage (III/2)	400 V
Rated surge voltage (III/2)	4 kV

#### Air clearances and creepage distances

Insulating material group	I
Voltage	250 V
Rated insulation voltage (III/3)	250 V
Rated insulation voltage (III/2)	400 V
Rated insulation voltage (II/2)	630 V
Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV

#### Standards and Regulations

Connection in acc. with standard	EN-VDE	
	CSA	
Flammability rating according to UL 94	V0	

#### **Environmental Product Compliance**

REACh SVHC	Lead 7439-92-1	
China RoHS	Environmentally Friendly Use Period = 50	



### Technical data

**Environmental Product Compliance** 

For details about hazardous substa Category "Manufacturer's declarati	•
--	---

## **Approvals**

Approvals

Approvals

DNV GL / CSA / IECEE CB Scheme / SEV / EAC / cULus Recognized

Ex Approvals

#### Approval details

DNV GL http://exchange.dnv.com/tari/ TAE00001	= V
---	-----

CSA <b>(3)</b>	http://www.csagroup.org/services-industries/product-listing/ 13631	
	D	В
Nominal voltage UN	300 V	300 V
Nominal current IN	10 A	10 A
mm²/AWG/kcmil	28-12	28-12

IECEE CB Scheme	<b>CB</b> scheme	http://www.iecee.org/	CH-8225
Nominal voltage UN		250 V	
Nominal current IN		28 A	
mm²/AWG/kcmil		4	

SEV	SEV	https://www.electrosuisse.ch/de/meta/shop/produktezertifikate.html IK-3542-M1		IK-3542-M1
Nominal voltage UN			250 V	
Nominal current IN			28 A	
mm²/AWG/kcmil			4	



## **Approvals**



cULus Recognized <b>GFL</b> US	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E60425-19770427	
	D	В
Nominal voltage UN	300 V	300 V
Nominal current IN	10 A	15 A
mm²/AWG/kcmil	30-12	30-12

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com