


VICOR CONFIDENTIAL


THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR
HEREWITH IS NOT TO BE REPRODUCED, USED OR
DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT
THE PERMISSION OF VICOR CORP.

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
1	RELEASED PER E060499 PEI	02/16/06	MB
2	REVISED PER E063650 PEI	03/13/06	MB
3	REVISED PER E060905 BW	07/28/06	MB
4	REVISED PER E072040 JS	09/06/07	SG
5	REVISED PER E091875 JS	10/20/09	REJH
6	REVISED PER E092163 GCK	12/04/09	MH
7	REVISED PER E101309 KUK	10/22/10	AR




REF:
ISOLATION INSULATOR (FR4)
SEE NOTES 5 & 7





WIRE GAUGE TABLE

PN#	WIRE GAUGE	PIN DIAMETER AFTER TINNING (+/- .003")
31741	#21	0.030"
31742	#19	0.036"
31743	#16	0.051"
31744	#16	0.051"



NOTES:

1. ASSEMBLY TO BE FREE OF NICKS.
2. WINDINGS TO BE EVENLY SPACED.
3. RoHS COMPLIANT. LEAD FREE PER CST-0001 LATEST REVISION.
4. GENERAL WORKMANSHIP STANDARDS FOR MAGNETIC COMPONENTS PER WS-0002.
5. ITEMS 3 & 4 SUPPLIED BY VENDOR AT ASSEMBLY.
6. ALL PARTS FLAME RATED MIN U.L. 94V-0.
7. APPLY ADHESIVE (ITEM 5) TO THE BASE OF ISOLATION INSULATOR (ITEM 3) AND TO ALL LEADS ON THE TOP SURFACE OF THE BOARD.
8. ◯ DENOTES CRITICAL CHARACTERISTIC FOR LOT INSPECTION.
9. SEE TABLE FOR WIRE GAUGE DIMENSIONS.
10. LEADS MAY BE TINNED WITH SN96/AG4 OR SAC305 (SN 96.5, AG 3.0, CU 0.5) OR VICOR APPROVED EQUIVALENT.
11. DIMENSIONS ARE INCHES ONLY.

DRAWN	DATE	<div> VICOR</div>			SWD
P.E.IENI	11/02/05				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE INCH [MM] TOLERANCES ARE: DECIMALS ANGLES X.XX [X.X] = ±0.01 [0.25] ±1° X.XXX [X.XX] = ±0.005 [0.127]		<div>IND TOR 1.03 DIA 2W ASSY DWG</div>			
THIRD ANGLE PROJECTION <div></div> DO NOT SCALE DRAWING					
		SCALE 2 : 1			SHEET 1 OF 1