TCSMCN1F9M2P



Main

Range of product	OsiSense XG	
Accessory / separate part category	Connection accessories	
Accessory / separate part type	Connecting cable	
Accessory / separate part designation	Modbus shielded connecting cable	
Accessory / separate part destination	PLC Tap-off box	
Cable length	6.56 ft (2 m)	

Complementary

Product compatibility	TCSAMT31FP	
Electrical connection	1 connector M12 straight (A coding) 1 male connector mini DIN 8 pins straight (A coding)	
Color	Black	
Product weight	0.77 lb(US) (0.35 kg)	

Environment

IP degree of protection	IP67
-------------------------	------

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0627 - Schneider Electric declaration of conformity	Compliant - since 0627 - Schneider Electric declaration of conformity
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period 18 months	
---------------------------	--

Wiring Diagram

Modbus Connections



Pin no.		Signal
1	-	Drain (Modbus-SHLD)
2	Red	+ 24 VDC
3	Black	0 V/Modbus-GND

4	White	D0
5	Blue	D1
Connector casing		Shielding