



SIGN	DATE	DESCRIPTION	APPROVER
△	4/01'09	Current, wire range, torque, safety approval are changed	Jody
△	11/17'09	Wire guard solder pin is changed from Brass to Copper	Aaron
△	04/04'11	Add is spec.	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
- Item 2 Coamp : Steel stamping , Zinc plated
- △ ● Item 3 Wire guard solder pin : Copper ,Tin plated
- Item 4 Terminal screw: Steel Zinc plating"- "slot type

- Electrical cULs IEC
- Voltage rating : 600V 1000V
 - △ ● Current rating : 65A 76A
 - Wire range : 16.00mm²
 - Solid wire (AWG) : 6-20
 - Stranded wire (AWG) : 6-20
 - △ ● Torque (LB-In.) : 19LB-In
 - Screw : M4.5
 - Wire strip length : 10-11mm
 - Withstanding voltage : 2.2KV 6KV
 - Operating temperature : -40°C+115°C
 - Soldering temperature : 250°C+10°C/5 Sec
 - Safety Approval : US

VP xx 85 x 7 xxxx G

RoHS
Pb<40,000ppm

0000 Standard @ Logo
000A Standard ANY Logo
Any special item by customer request, please contact sales department.

NO of poles
02 2 CONTACTS 0: Black
03 3 CONTACTS 5: Green (RAL 6018/T)
... .. 6: Blue
12 12 CONTACTS 8: Grey (RAL 7035/D)

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	25.40	38.10	50.80	63.50	76.20	88.90	101.60	114.30	127.0	139.70	152.40
Dim B	12.70	25.40	38.10	50.80	63.50	76.20	88.90	101.60	114.30	127.0	139.70
TOL	±0.15			±0.20			±0.30				

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		VP 12.70 Series (Double tail 0.9x1.0) Contacts Pin Pitch 4.0mm				
PART NO.	VPxx85x7xxxxG	DWG NO.	8VP0105			
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
			Chen Bo 2011.04.04		X. ±0.50	
					UNIT: mm	X.X ±0.30
				SHEET: 01/01	X.XX ±0.10	
				REV.: E	X° ±1°	