


**SERIES:** TBL002A-350 | **DESCRIPTION:** TERMINAL BLOCK**FEATURES**

- 1~24 poles
- 45° angle with board
- interlocking (side)
- push button clamp
- 3.50 mm pitch
- UL and CE safety approvals

**SPECIFICATIONS**

| parameter                   | conditions/description                      | min | typ  | max  | units |
|-----------------------------|---------------------------------------------|-----|------|------|-------|
| rated voltage (per contact) | UL                                          |     |      | 300  | V     |
|                             | IEC                                         |     |      | 400  | V     |
| rated current (per contact) | UL                                          |     |      | 2    | A     |
|                             | IEC                                         |     |      | 5    | A     |
| withstanding voltage        |                                             |     | 2000 |      | Vac   |
| surge voltage               |                                             |     |      | 4000 | V     |
| contact resistance          |                                             |     |      | 20   | mΩ    |
| insulation resistance       | at 500 Vdc                                  | 500 |      |      | MΩ    |
| operating temperature       |                                             | -40 |      | 105  | °C    |
| safety approvals            | UL 1059, EN 60998-1:2004, EN 60998-2-1:2004 |     |      |      |       |
| flammability rating         | UL94V-0                                     |     |      |      |       |
| RoHS                        | yes                                         |     |      |      |       |

**SOLDERABILITY**

| parameter      | conditions/description | min | typ | max | units |
|----------------|------------------------|-----|-----|-----|-------|
| hand soldering | for maximum 10 seconds | 345 | 350 | 355 | °C    |
| wave soldering | for maximum 5 seconds  | 255 | 260 | 265 | °C    |

**PART NUMBER KEY****TBL002A-350 - XX XX - 2XX**

Base Number

No. of Poles:

|    |    |    |
|----|----|----|
| 01 | 09 | 17 |
| 02 | 10 | 18 |
| 03 | 11 | 19 |
| 04 | 12 | 20 |
| 05 | 13 | 21 |
| 06 | 14 | 22 |
| 07 | 15 | 23 |
| 08 | 16 | 24 |

Body Color:

BE = blue  
GR = green  
OR = orange  
YL = yellow  
\*GY = gray  
BK = black

Push Button Color:

BE = blue  
GR = green  
OR = orange  
YL = yellow  
\*GY = gray  
BK = black  
WT = white

\*Standard housing color is gray with gray push button. All other colors are subject to higher MOQ. Please inquire with CUI Devices sales for details.

## MECHANICAL DRAWING



units: mm

tolerance (per module):

 $X \leq 6.00$ :  $\pm 0.25$  mm $6.00 < X \leq 30.00$ :  $\pm 0.40$  mm





unless otherwise noted

| DESCRIPTION | MATERIAL        | PLATING/COLOR |
|-------------|-----------------|---------------|
| housing     | PA66 (UL94V-0)  |               |
| contacts    | phosphor bronze | tin           |



A pin  
when N is even, the number is N/2;  
when N is odd, the number is (N+1)/2.

B pin  
when N is even, the number is N/2;  
when N is odd, the number is (N-1)/2.



| WIRE ASSEMBLY |           |                          |
|---------------|-----------|--------------------------|
|               | UL        | IEC                      |
| Wire Range    | 24~20 AWG | 0.2~0.75 mm <sup>2</sup> |
| Strip Length  | 8~9 mm    |                          |

This series is constructed of 1 pole modules where L is the total length, P is the pitch, and N is the number of poles.

| N | 01    | 02    | 03    | 04    | 05    | 06    | 07    | 08    | 09    | 10    | 11    | 12    |
|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| L | 5.00  | 8.50  | 12.00 | 15.50 | 19.00 | 22.50 | 26.00 | 29.50 | 33.00 | 36.50 | 40.00 | 43.50 |
| B | --    | 3.50  | 7.00  | 10.50 | 14.00 | 17.50 | 21.00 | 24.50 | 28.00 | 31.50 | 35.00 | 38.50 |
| N | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20    | 21    | 22    | 23    | 24    |
| L | 47.00 | 50.50 | 54.00 | 57.50 | 61.00 | 64.50 | 68.00 | 71.50 | 75.00 | 78.50 | 82.00 | 85.50 |
| B | 42.00 | 45.50 | 49.00 | 52.50 | 56.00 | 59.50 | 63.00 | 66.50 | 70.00 | 73.50 | 77.00 | 80.50 |

## REVISION HISTORY

| rev. | description       | date       |
|------|-------------------|------------|
| 1.0  | initial release   | 04/17/2019 |
| 1.01 | brand update      | 02/06/2020 |
| 1.02 | updated datasheet | 04/20/2020 |

The revision history provided is for informational purposes only and is believed to be accurate.

---

# CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.