

1		2		3		4		5		6		7		8	
REV.				ECN NO.		DATE		SIGN		DESCRIPTION					
A						2019-05-14		Allen Pan		01版轉A					
Housing Clamp Ring Gasket Nut M12*1.0 M17*1.0 M16*1.0 20.1 65(Ref) Pin Assignments Front View ALTW CONFIDENTIAL 2019-05-14 R&D DEPT.															
Notes: * Waterproof Rate: IP68(1M, 24Hour). * Gasket: Rubber, Gray * Nut: Thermoplastic, Black. * Rated Voltage: 60V. * Rated Current: 4A. * Gasket For Cable OD: $\varnothing 4.0\text{mm} \sim \varnothing 8.0\text{mm}$. * Applicable Wire Gauge: 22AWG. * Operating Temperature: $-40 \sim 85^{\circ}\text{C}$ * Insulation Resistance: $\geq 100\text{M}\Omega$. * Insertion/Withdrawal Cycles: ≥ 100. * Nut Recommended Tightening Torque: 4~6kgf.cm. * Wire Pulling Force: $\geq 20\text{N}$. M 12A - 05 B M M E - S L 8 001 12A:A-Code 05:5Pin B:Without S/R(無網尾) M:Male Connector(公座) M:Male Pin(公Pin) E:Push in Type(組裝式) 001:Without Cable 8:IP68(防水等級68) L:Straight(180°) S:Screw(螺紋式)															
UNIT:mm TOLERANCE $\pm 0.5\text{mm}$ TITLE M12 A Code Push in Type Assy 5Pin M Conn M Pin SCALE 1:1 SIZE A4 SHEET 1 OF 1 REV. A WC-REV. A.4 QC:Inspection item Amphenol LTW 安費諾亮泰企業股份有限公司 ITEM NO M12A-05BMME-SL8001 DWG NO M12A-05BMME-SL8001 CUSTOMER ALTW DRAWN BY Allen Pan CHECKED BY Fred Lee APPROVED BY Fred Lee DATE 2019-05-14 DATE 2019-05-14 DATE 2019-05-14															
1		2		3		4		5		6		7		8	

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.