




PERFORMANCE CHARACTERISTICS

CURRENT RATING 1.5A AT 20°C (FULLY LOADED)
1 A AT 70°C (FULLY LOADED)
RATED VOLTAGE : 500 V AC (CONT /CONT)
OPERATING TEMPERATURE : -55°C TO 125°C
CONTACT RESISTANCE 20 mΩ MAX
INSERTION FORCE : 0.75N MAX/CONT
EXTRACTION FORCE : 0.15N MIN/CONT
INSULATION RESISTANCE : 10⁴ MΩ MIN

- NOTES 1. " " LEAD FREE INDICATOR : LF=LEAD FREE
PERFORMANCE LEVEL INDICATION (REF DWG NO.BSC .201844.003)
2. THIS PRODUCT IS CSA APPROVED.
THIS PRODUCT IS UL RECOGNIZED.
3. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS.A.201572.001
4. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

rev	ecn no	dr	date
A	CONVERSION REVISION 05	KN	14-09-01
B	105-0093	MINI	08-06-05
C	DG05-0278	Kason	02-08-05
-	-	-	-
-	-	-	-
-	-	-	-
05	Improved Cover Added	R.M	110601

Material			Spec ref				
Mat code			✓	tolerance IDEC ± 0.2 IDEC 2DEC ± 0.1 2DEC ANGLES ± 1° HOEKEN	projection 	MM 	
Heattreat							
Plating/Finish							
Dr	W. Panis	07-04-92			size A4	Scale 2.000	
Eng			Product family MILLIPACS				
Chr			Model Name		ECN	DG05-0278	
Appr			Model Revision		REL Level		
		title MPACS 5+2R RA RCP CONN TYPE C			dwg no BSC201418003		Rev C
Pro/E file	catalog	BDM: BSC201418003		CUSTOMER DRAWING		sheet 1 of 1	