

RJ45-FT RJ45 Feed Thru

Smart Technology. Delivered.



IP67 RATED OUTDOOR RJ45 FEED THRU

Laird's RJ45-FT feedthru allows for quick installation of ethernet cables on outdoor equipment or indoor equipment. The feedthru allows for pass thru of the RJ45 connector and sealing of the cable for a weatherproof installation.

FEATURES **✓** RoHS

- Pass-thru of RJ45 shielded or unshielded connectors
- Clamps securely to 5 mm min. diameter cables
- Constructed of UV protected materials for long life in harsh outdoor environments.
- Seal meets IP67 criteria.
- · Shock and vibration resistant.
- UL and CE rated

MARKETS

- · Wireless base stations
- · Wireless client radios
- Direct burial equipment
- · Industrial process control
- Telecom equipment
- 802.11 a/b/g wireless Systems
- 10BaseT, 100BaseT or 1000BaseT networks
- · Factory automation
- WiMAX

SPECIFICATIONS	
Material	UV Resistant Nylon 66 and EPDM rubber
Sealing	IP67
Salt Spray	>1000 h
Flammability	UL94VO
Thermal Shock	10 cycles -40 to +100°C
Temperature Range	-40°C to +85°C
Installation Hole Dia	0.787 in (20 mm)
Overall Size (L x Dia)	1.75 x 1 in (44 x 25 mm)
Weight	.5 oz (14 gm)

SYSTEM ORDERING INFORMATION

RJ45-FT RJ45 waterproof outdoor cable feedthru - 10 pack

NOTES

• All shipments F.O.B. Schaumburg, IL 60173











Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-RJ45-FT 0115

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidant or consequential damages of any kind. All Laird products are solid pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird logo, and other marks are trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.