







- 1 MATERIAL:
HOUSING: LCP, GLASS FILLED, UL94V-0.
TERMINALS: HIGH PERFORMANCE COPPER ALLOY.
- 2 FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN
ON PCB TAILS, NICKEL OVERALL.
- 3 FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN-LEAD
ON PCB TAILS, NICKEL OVERALL.
4. SCREWS PACKAGED IN END OF PACKAGING TUBE.
- 5 FOR GROUNDED GUIDE PIN USE Ø3.56±0.08 PTH,
Ø3.66 DRILL, AND Ø6.5 PAD.
6. KEYING PIN SHOWN IN POSITION A, SEE KEYING CHART
ON SHEET 2 FOR OTHER POSITIONS.



RIGHT GUIDED
BACKPLANE HOLE PATTERN
(CONNECTOR SIDE)



THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN J. K. SHOBER 25JAN2011	TE Connectivity	
DIMENSIONS:		CHK J. EABY 25JAN2011	NAME	
mm		APVD J. EABY 25JAN2011	IMPACT, 6 PAIR, 16 COLUMN, HEADER	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	RIGHT GUIDED, LEFT END WALL	
9 PLC ±.05		APPLICATION SPEC	SIGNAL MODULE, 0.39 PTH	
1 PLC ±0.25		WEIGHT	SIZE CAGE CODE DRAWING NO	
3 PLC ±0.13		CUSTOMER DRAWING	A100779C=2007895	
5 PLC ±.05		SCALE 4:1	SHEET 1 OF 2	
4 PLC ±.05		REV B		
ANGLES				
FINISH				
SEE TABLE				

LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	OWN	APVD
			-	SEE SHEET 1	-	-	-

	H	5.5	8-2007895-6
	H	4.9	8-2007895-5
	H	4.5	8-2007895-4
	H	5.5	8-2007895-3
	H	4.9	8-2007895-2
	H	4.5	8-2007895-1
	G	5.5	7-2007895-6
	G	4.9	7-2007895-5
	G	4.5	7-2007895-4
	G	5.5	7-2007895-3
	G	4.9	7-2007895-2
	G	4.5	7-2007895-1
	F	5.5	6-2007895-6
	F	4.9	6-2007895-5
	F	4.5	6-2007895-4
	F	5.5	6-2007895-3
	F	4.9	6-2007895-2
	F	4.5	6-2007895-1
	E	5.5	5-2007895-6
	E	4.9	5-2007895-5
	E	4.5	5-2007895-4
	E	5.5	5-2007895-3
	E	4.9	5-2007895-2
	E	4.5	5-2007895-1
	D	5.5	4-2007895-6
	D	4.9	4-2007895-5
	D	4.5	4-2007895-4
	D	5.5	4-2007895-3
	D	4.9	4-2007895-2
	D	4.5	4-2007895-1
	C	5.5	3-2007895-6
	C	4.9	3-2007895-5
	C	4.5	3-2007895-4
	C	5.5	3-2007895-3
	C	4.9	3-2007895-2
	C	4.5	3-2007895-1
	B	5.5	2-2007895-6
	B	4.9	2-2007895-5
	B	4.5	2-2007895-4
	B	5.5	2-2007895-3
	B	4.9	2-2007895-2
	B	4.5	2-2007895-1
	A	5.5	1-2007895-6
	A	4.9	1-2007895-5
	A	4.5	1-2007895-4
	A	5.5	1-2007895-3
	A	4.9	1-2007895-2
	A	4.5	1-2007895-1
	-	5.5	2007895-6
	-	4.9	2007895-5
	-	4.5	2007895-4
	-	5.5	2007895-3
	-	4.9	2007895-2
	-	4.5	2007895-1
FINISH	KEY POSITION	DIM M	PART NUMBER

REFER TO WWW.TE.COM
FOR PRODUCT AVAILABILITY

KEY POSITION
CHART

NONE

A

E

B

F

C

G

D

H

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN J. K. SHOBER 25JAN2011	TE Connectivity	
DIMENSIONS:		CHK J. EABY 25JAN2011	NAME	
mm		APVD J. EABY 25JAN2011	IMPACT, 6 PAIR, 16 COLUMN, HEADER RIGHT GUIDED, LEFT END WALL SIGNAL MODULE, 0.39 PTH	
		PRODUCT SPEC	SIZE	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	CAGE CODE	
9 PLC ±.013		WEIGHT	DRAWING NO	
3 PLC ±0.13		A100779C=2007895		
5 PLC ±.013		RESTRICTED TO		
4 PLC ±.013		CUSTOMER DRAWING		
ANGLES		SCALE		
FINISH		5:1		
SEE TABLE		SHEET		
		2 OF 2		
		REV		
		B		