


CABLE ACCEPTANCE DIMS.

JACKET DIA. .088 MAX.  
 DIELECTRIC DIA. .038 MAX.  
 CENTER COND. DIA. .015 MAX.



REVISIONS

ZONE	LTR	DESCRIPTION	DATE	APPROVED
	G	REDRAWN & UPDATED: ITEMS 4, 7, 8, 9 SPEC. WAS TEFLOX - MIL-M-14077: ITEMS 1, 2, 3, 5, 6, 8, 9 DELETED "F.M." FROM SPEC. NOTES 1 & 3, "MALCO" WAS "MICRODOT"; NOTE 3, 010-0003-0000 WAS 010-0003: (REV. (ECO 19702))	5/19/75	[Signature]
	H	ITEM 6, WAS 003-0031-0000	3/2/97	[Signature]
	J	NOTE 2: RF-ASMB-89 WAS BULLETTIN #48	4/2/05	[Signature]

NOTES: (UNLESS OTHERWISE SPECIFIED)

- THIS CONNECTOR MATES WITH ALL S-50 JACKS AND RECEPTACLES AS LISTED IN MALCO CATALOG.
- FOR ASSEMBLY INSTRUCTIONS SEE RF-ASMB-89
- MALCO ASSEMBLY TOOL #T-3221 OR 010-0003-0000.
- OPTIONAL, DEPENDING ON CUSTOMER REQUIREMENTS.
- SILVER PLATE .0002-.0004 PER QQ-B-365.
- GOLD PLATE .00005 MIN. PER MIL-G-45204, TYPE II, CL. I.
- 10-32 UNF-2B THD

FINISH	QTY.	ASTERISK No. *	PT. NO.	DESCRIPTION	MAT'L & SPEC.	ITEM NO.
	1	1	003-0270-0000	BEND RELIEF CAP	SILICONE RUBBER ZZ-E-705	9
	1	1	003-0153-0001	BUSHING	TEFLOX L-P-403	8
	1	1	003-0597-0001	FERRULE PIN PROTECTOR	TEFLOX L-P-403	7
	1	1	003-0163-0001	RING	BRASS QQ-B-626	6
	1	1	005-0355-0001	FERRULE	BRASS QQ-B-626	5
	1	1	003-0205-0001	BUSHING	TEFLOX L-P-403	4
	1	1	003-0360-0002	PIN	BRASS QQ-B-626	3
	1	1	003-0772-0001	1" HEX NUT - WITH SAFETY WIRE HOLES	BRASS QQ-B-626	2
	1	1	003-0454-0001	1" HEX NUT	BRASS QQ-B-626	1

PARTS LIST

CONTRACT NO.		DATE	
APPROVALS	DATE	APPROVED	DATE
CHECKED	1/19/58	PR. ENG. [Signature]	
MATERIAL		FINISH	
NOTED		NOTED	
DO NOT SCALE DRAWING		APPLICATION	
USED ON		NEXT ASSY	

MALCO A MICRODOT COMPANY, INC. 220 PASADENA AVE., SO. PASADENA, CALIF. 9103	
SIZE	CODE IDENT NO.
B	98278
DRAWING NO. 052-0235-000*	
PROJ. NO.	CD
93	
53	
200	
100	

TYCO CUSTOMER DRAWING  
 5-1532146-1