XUYAFPCO966S



Main

Range of product	OsiSense XU
Series name	Application assembly
Specific application of photoelectric detector	Detection of objects on small conveyor Detection of reference and colour marks in packaging Monitoring position or presence of parts on an assembly or packing machine Use of fiber optics in vibratory environments (robot arms)
Sensor name	XUY
Sensor design	Fiber design
Emission	Red LED

Complementary

Electronic sensor type	Photo-electric sensor
Material	Plastic
Enclosure material	Polycarbonate
Pulse frequency	8 kHz
Type of output signal	Discrete
Output type	Solid state
Discrete output function	1 NO or 1 NC programmable
Discrete output type	PNP and NPN
Electrical connection	1 male connector M8, 4 pins
Cable length	6.56 ft (2 m)
Supply circuit type	DC
[Us] rated supply voltage	1224 V DC with reverse polarity protection
Supply voltage limits	1030 V DC
Voltage state 0 guaranteed	< 1.4 V
Voltage state 1 guaranteed	> 3 V
Switching capacity in mA	100 mA for overload and short-circuit protection
Switching frequency	< 1 kHz
Voltage drop	< 2 V (closed state)
Current consumption	<= 40 mA (no-load)
Delay response	<= 5 ms for plastic fibre optics 2.2 mm
Delay recovery	<= 5 ms for plastic fibre optics 2.2 mm
Setting-up	Sensitivity adjustment using +/- teach mode
Display type	Bar graph
Product weight	0.12 lb(US) (0.056 kg)

Environment

LITTII OTTIII CITE		i
product certifications	CE CULus	
ambient air temperature for operation	32140 °F (060 °C)	
ambient air temperature for storage	-4176 °F (-2080 °C)	
immunity to ambient light	<= 10000 lux with natural light <= 20000 lux with incandescent bulb	
IP degree of protection	IP65 conforming to IEC 60529	

Offer Sustainability

Not Green Premium product Not Green Premium product



Compliant - since 0707 - Schneider Electric declaration of conformity	Compliant - since 0707 - Schneider Electric declaration of conformity
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov
Contractual warranty	
Warranty period	18 months

