

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOCAD

DIST00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	AL2	REVISED PER ECO-11-004820	11MAR11	RK	HMR

DATE CODE

AMP XXXX
3-435802-8
OFF

PIN 1 IDENT DOT

.38±.02

.022±.002 TYP

.100 TYP

A±.02

FIG 1

CONTACT ARRANGEMENT

FIG 2

435802-1 SHOWN

CLOSE
OPEN

.14±.02 TYP

.012 TYP

.19±.01

.315±.010

.02^{+.01}_{-.00} STANDOFF, 4 PLC

.29±.02 TYP

MOUNTING SURFACE

FIG 1

CONTACT ARRANGEMENT

CLOSE
OPEN

.14±.02 TYP

.012 TYP

.19±.01

.315±.010

.02^{+.01}_{-.00} STANDOFF, 4 PLC

.29±.02 TYP

MOUNTING SURFACE

FIG 2

435802-1 SHOWN

7

NO POSITION MARKING.

8

NO PART NO. MARKING.

9

STRIPPABLE TAPE SEAL, SEE FIGURE 8.

10

OBSOLETE PARTS: OBSOLETE CIS
STREAMLINING PER D.RENAUD/D.SINISI

1

FOR ADDITIONAL SPECIFICATIONS SEE AMP PRODUCT SPEC 108-7519.

2

SWITCH SHOWN IN OPEN POSITION.

3

ALL CHARACTERS AND ROCKERS ARE WHITE, HOUSING IS BLACK.

4

STAMPING WILL VARY ON 2 AND 3 POSITION TOPS DUE TO SPACE RESTRICTIONS.

5

STRIPPABLE TRANSPARENT SEAL, SEE FIG 6.

6

.315 DIMENSION APPLIES AT TERMINAL TIPS.
TERMINALS ARE .300^{+.010}_{-.000} AT MOUNTING SURFACE.

	FIG 2	FIG 3A& 7		1.08	10	6-435802-3
	FIG 1	FIG 3B	9	.88	8	3-435802-8
	FIG 2	7 8	5	.58	5	3-435802-1
	FIG 2	7 8	5	.88	8	3-435802-0
	FIG 2	7 8	5	.48	4	2-435802-9
	FIG 1	7	5	.28	2	2-435802-8
	FIG 1	7	5	.28	2	2-435802-7
	FIG 2	7	5	1.08	10	2-435802-6
	FIG 2	FIG 4		.88	8	2-435802-5
	FIG 2	7	5	.88	8	2-435802-4
	FIG 2	FIG 3A& 5		.48	4	2-435802-3
	FIG 2			1.28	12	2-435802-2
	FIG 2			1.18	11	2-435802-1
	FIG 2			1.08	10	2-435802-0
	FIG 2	FIG 3A	5	.98	9	1-435802-9
	FIG 2			.78	7	1-435802-8
	FIG 2			.68	6	1-435802-7
	FIG 2			.58	5	1-435802-6
	FIG 2			.48	4	1-435802-5
	FIG 2		5	.38	3	1-435802-4
	FIG 1	FIG 3B	5	.28	2	1-435802-3
	FIG 1	FIG 3B		1.28	12	1-435802-2
	FIG 2	FIG 3B	5	.28	2	1-435802-0
	FIG 2	FIG 3A		.88	8	435802-9
	FIG 2	FIG 3A		1.08	10	435802-8
	FIG 2	FIG 3A		.98	9	435802-7
	FIG 2	FIG 3A		.78	7	435802-6
	FIG 2	FIG 3A		.68	6	435802-5
	FIG 2	FIG 3A		.58	5	435802-4
	FIG 2	FIG 3A		.48	4	435802-3
	FIG 2	FIG 3A		.38	3	435802-2
	FIG 2	FIG 3A		.88	8	435802-1
	HOUSING	MARKING	PROTECTIVE SEAL	A	NO OF POSN	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN R. TALLEY 9-19-89

CHK R. MILLER 9-19-89

APVD H. LEITER 9-19-89

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS: INCHES

0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± .005
4 PLC ± -
ANGLES ± -

FINISH CONTACTS: PLATED .000030 MIN GOLD IN CONTACT AREA OVER .000050 MIN NICKEL

TE Connectivity

SWITCH ASSY, DIP, TYPE C, 7000 SERIES, SPST, SIDE ACTUATED

SIZE A2 CAGE CODE 00779 DRAWING NO C=435802

RESTRICTED TO -

SCALE 4:1 SHEET 1 of 2 REV AL2




FIG 3A




FIG 3B




FIG 4





FIG 5



PROTECTIVE SEAL

FIG 6






FIG 7



PROTECTIVE SEAL

FIG 8

 $.010 \pm .010$ $.005^{+.010}_{-.005}$
TYP

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. TALLEY 9-19-89	 TE Connectivity								
		CHK R. MILLER 9-19-89									
DIMENSIONS: INCHES		APVD H. LEITER 9-19-89	NAME SWITCH ASSY, DIP, TYPE C, 7000 SERIES, SPST, SIDE ACTUATED								
		PRODUCT SPEC —									
		APPLICATION SPEC —									
		SIZE	CAGE CODE	DRAWING NO		RESTRICTED TO					
		MATERIAL		FINISH		WEIGHT	—				
SEE SHEET 1		SEE SHEET 1		CUSTOMER DRAWING		SCALE	4:1	SHEET	2 OF 2	REV	AL2