


Token Ring Isolation Modules

Single & Dual SMD Packages

HALO
ELECTRONICS, INC.




Product Features:

- Standard series of SMD Isolation Modules to meet the high isolation and impedance matching requirements of IEEE 802.5 for Token Ring applications.
- Non-Standard designs are also available.
- UL60950 and EN60950 recognized
- Patented Open Frame Construction
- 100% Compliance Testing
- 1500Vrms Hi-Pot


Part Number	Package Style	Turns Ratio $\pm 3\%$	PRI OCL ($\mu\text{H typ}$)	PRI/SEC Cw/w (pF max)	Primary LL ($\mu\text{H max}$)	PRI DCR ($\Omega \text{ max}$)	Rise Time (nS max)
TG11-0756N1LF	Dual	1:1:1:1	75	10	0.2	0.2	3.0
TG11-0756NTLF	Single	1:1:1:1	75	13	0.2	0.2	3.0
TG11-1506N1LF	Dual	1:1:1:1	150	10	0.2	0.3	3.5
TG12-0756N1LF	Dual	1:1:2:2	75	10	0.1	0.2	10
TG12-0756NTLF	Single	1:1:2:2	75	16	0.1	0.2	3.0
TG12-1506N1LF	Dual	1:1:2:2	150	12	0.1	0.3	10
TG51-0756N1LF	Dual	1:1:1.22:1.22	75	10	0.2	0.2	3.0
TG51-1506N1LF	Dual	1:1:1.22:1.22	150	12	0.3	0.3	3.5
TG51-2506N1LF	Dual	1:1:1.22:1.22	250	15	0.5	0.4	4.0

Please contact the factory or representative for individual datasheets or additional information.

Single Schematic




Dual Schematic



Token Ring Isolation Modules


Package NT



Recommended
Solder Pad Dimensions

Dimensions: inches [mm]
Co-Planarity: 0.004 [0.10]

Package N1



Recommended
Solder Pad Dimensions

Dimensions: inches [mm]
Co-Planarity: 0.004 [0.10]

US Patent Numbers

5,656,985 6,297,721 B1
6,297,720 B1 6,320,489 B1
6,344,785 B1 6,662,431 B1



2880 Lakeside Drive #116
Santa Clara, CA 95054
(650) 903-3800
www.haloelectronics.com

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC converters, and integrated Ethernet connectors. HALO's leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories offering high quality products at a competitive price.