





3 4 NOTES: I. MATERIAL: HOUSINGS: MODIFIED POLYPHENYLENE ETHER PADDLE CARD: PRINTED CIRCUIT SUBSTRATE HEAT SHRINK TUBE: POLYOLEFIN EPOXY LOCTITE 2. THIS PRODUCT MEETS THE RESTRICTION OF HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT (RoHS) DIRECTIVE (2002/95/EC) 3. THIS DIMENSION IS A FINISHED PRODUCT LENGTH. 4. UNLESS OTHERWISE SPECIFIED ASSEMBLED LENGTH TOLERANCE IS TO BE: "DIM L" < | METER = ±15mm "DIM L" | METER TO 10 METERS = \pm 2% OF "DIM L" 5. UNLESS OTHERWISE SPECIFIED LABEL POSITION IS TO BE 95mm FROM REAR OF PI CONNECTOR. LABEL DETAILS: MANUFACTURER CODE OR NAME COUNTRY OF ORIGIN CUSTOMER P/N OR FCI P/N REVISION DATE CODE (YYYY/MM/DD FORMAT) - SERIAL NUMBER FONT SHALL BE CLEARLY VISIBLE AND BLACK IN COLOR. 6. ALL CABLE ASSEMBLIES SHALL BE 100% TESTED FOR CONTINUITY AS DEFINED IN WIRING LIST. 7. ALL CABLE ASSEMBLIES SHALL BE 100% HI-POT TESTED BH APPLYING 300V DC FOR A MINUMUM OF 10ms. 8. IMPEDANCE: 100Ω DIFFERENTIAL. 9. OTHER TESTING PERFORMED AS REQUIRED BY PRODUCT SPECIFICATION: GS-12-650. 10. PACKAGE AND LABEL CABLE ASSEMBLIES PER GS-14-1272. II. A "∠-\" SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION. THE CURRENT REVISION WILL BE SHOWN IN THE SYMBOL. 12. "HLF" PRODUCT NUMBERS DESIGNATE THE USE OF HALOGEN FREE RAW CABLE. 13. HALOGEN FREE RAW CABLE CAN BE USED AS A SUBSTITUTE ON NON-HF PRODUCT NUMBERS. 14. PART NUMBER/SUPPLIER SUBSTITUTION IS NOT ALLOWED. Copyright projection dr Andy Wu spec ref size scale D mm A 3 eng Andy Wu 1:1 tolerance sto \oplus TOLERANCES UNLESS ELX-N-13885-1 chr ecn no ISO 406 OTHERWISE SPECIFIED ISO 1101 appr | Roger Cheng product family rel level Released 0.X ± 0.3 mSAS HD INTERNAL (4i) 10123416 0.XX surface 0.XXX ±0.005 CABLE ASSEMBLY- 6 Gb/s, short type ISO 1302 Product - Customer Drw sheet 4 of 4 www.fci.com | cat. no. angular Pro/F File - REV C - 2009-06-09

3

PDS: Rev:B

STATUS:Released

Printed: Jan 21, 2013