






PART NUMBER SEE SHEET 2



spec ref				dr	Rainbow Zhan	2016/10/10	projection	MM	size	A3	scale	3:2
tolerance std ISO 406 ISO 1101	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Vickling Liu	2016/10/31			ecn no -			
				chr	Fancy Zhang	2016/10/31			rel level Released			
				appr	Pei-Ming Zheng	2016/10/31			product family PwrBlade+			
surface ISO 1302	linear	0.X	±0.5	Amphenol FCI	title 5ACP + 16S VERTICAL PLUG PF				dwg no 10106121-5004001	rev A		
		0.XX	±0.25									
		0.XXX	±0.10									
	angular	0°	±2°	cat. no.	Product - Customer Drw						sheet 1 of 3	

PRODUCT NO.	ROWS	HIGH POWER SIGNAL										CODE	DESCRIPTION
		E1	P1	P2	P3	P4	P5	1	2	3	4		
10106121-5004001LF	D C B A		H4	H4	H4	H4	H4	G	G	G	G		
								G	G	G	G		
								G	G	G	G		
								G	G	G	G		



spec ref				dr		Rainbow Zhan	2016/10/10		projection		MM		size		A3	scale		3:2									
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng		Vicking Liu	2016/10/31				ecn no					-									
ISO 406						chr		Fancy Zhang	2016/10/31																		
ISO 1101						appr		Pei-Ming Zheng		2016/10/31			product family					PwrBlade+					rel level		Released		
surface		linear		0.X		±0.5		Amphenol FCI		title		5ACP + 16S					dwg no		10106121-5004001					rev		A	
				0.XX		±0.25																					
				0.XXX		±0.10																					
ISO 1302		angular		0°		±2°				cat. no.		Product - Customer Drw					sheet 2 of 3										

NOTES:

- 1) PRODUCT MARK:
PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE .
THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.
- 2) MATERIALS:
-HOUSING : HIGH TEMP THERMOPLASTIC WITH GLASS FIBER, UL94V-0, BLACK.
-POWER CONTACT : HIGH CONDUCTIVITY COPPER ALLOY.
-SIGNAL CONTACT : COPPER ALLOY.
- 3) PLATING SPECIFICATION : 10116351
- 4) DENOTES CONNECTOR KEEP OUT ZONE.
- 5) DATUM AND BASIC DIMENIONS ARE ESTABLISHED BY CUSTOMER.
- 6) ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.
- 7) 1.15+/-0.025MM DRILLED HOLE PLATED WITH 0.00762MM MIN SN
OVER 0.0254-0.0762MM CU PLATING TO ACHIEVE A 1.02+/-0.07MM HOLE.
- 8) THIS PRODUCT MEETS EUROPEN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-47-0004.
- 9)PRODUCT SPECIFICATION : GS-12-658.
APPLICATION SPECIFICATION : GS-20-141.
PRODUCT PACKAGE SPECIFICATION: GS-14-1502.

spec ref				dr		Rainbow Zhan	2016/10/10		projection		MM		size		A3	scale		3:2	
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng		Vicking Liu	2016/10/31						ecn no				-
ISO 406						chr		Fancy Zhang	2016/10/31						rel level				Released
ISO 1101						appr		Pei-Ming Zheng	2016/10/31										product family
surface			linear	0.X	±0.5	Amphenol FCi		title	5ACP + 16S VERTICAL PLUG PF				dwg no	10106121-5004001				rev	A
				0.XX	±0.25														
				0.XXX	±0.10														
ISO 1302		angular	0°	±2°					cat. no.		Product - Customer Drw				sheet 3 of 3				