SIGN	DATE	DESCRIPTION	APPROVER
1			
2			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!









SECTION A-A

Material:

- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
- Item 2 Clamp : Steel stamping , Zinc plated
- Item 3 Wire guard solder pin : Copper , Tin plated
- Item 4 Terminal screw: Steel Zinc plating"-"slot type

Electrical	cULus	IEC
Voltage rating : 300V		250V
Current rating : 65A		57A

- Wire range :
- Solid wire (AWG) : 6-20 / 0.5-16mm ^{2}
- Stranded wire (AWG) : 6-20 / 0.5-16mm^2
- Torque (LB-In.) : 19 Lb-In / 1.2 N.m
- Screw : M4.5
- Wire strip length : 10~11mm
- Withstanding voltage : 1.6KV / 6KV
- Operating temperature : -40°C+115°C
- Soldering temperature : 250°C+10°C/5 Sec
- Safety Approval : c UL us

VP xx 6 5 x 8 xxxx G

- xx: No. of poles end stackable sesign
  - 02 2 CONTACTS
  - 03 3 CONTACTS
  - ... ...
  - 12 12 CONTACTS
- x:
  - 0 Black (RAL9005)
  - 2 Red (RAL3001/D)
  - 3 Orange(RAL2011/P)
  - 4 Yellow(RAL1018/A)
  - 5 Green(RAL6018/T)
  - 6 Blue (RAL5015/A)
  - 8 Grey(RAL7035/D)
- xxxx: 0000:"@"Logo (Standard)
  000A:"ANYTEK"Logo
  Any special item by customer request, please contact sales department.
- G: RoHS Pb<40,000ppm

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76	121.92
Dim B	10.16	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76
TOL	±0.20			±0.30				±0.40			

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	VP 10.16 Series 2P-12P (pitch=4.00 Double parallel tail)				
PART NO.	VPxx65x8xxxxG			DWG NO.	8VP0008
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Aaron 2010.12.02	Aaron 2010.12.02	UNIT: mm / SCALE: NONE / SHEET: 01/01 / REV.: B	

Tolerance	
X.	±0.50
X.X	±0.30
X.XX	±0.10
X°	±1°