

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A1	ECR-15-010494		14JUL2015	DW	CW
B	ECR-15-013292		24SEP2015	DL	CW
B1	ECR-15-017530		02DEC2015	GY	CW
B2	ECR-16-015492		08NOV2016	QY	CW

M4 SCREW RECOMMENDED
TIGHTENING TORQUE 1.2Nm
M4 螺丝, 推荐锁紧力矩 1.2Nm

4X M3 SCREW RECOMMENDED
TIGHTENING TORQUE 0.5Nm
4X M3螺丝, 推荐锁紧力矩 0.5Nm

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 250 V
RATED CURRENT: 10 A
INSULATION RESISTANCE: $\geq 400\text{M}\Omega$
RATED IMPULSE VOLTAGE: 4 KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: 0.14-2.5 mm² (26-14 AWG)
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20200X10XX000)


注释:

- 技术参数:
绝缘材料: PC
额定电压: 250V
额定电流: 10A
绝缘电阻: $\geq 400\text{M}\Omega$
额定脉冲电压: 4 KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
接线范围: 0.14-2.5 mm² (26-14 AWG)
接线类型: 冷压接
- 端子需要单独订购.
(订货号参考图面: T20200X10XX000)

TYPE-1, T2020402101-000, TE LOGO
类型-1, T2020402101-000, TE LOGO

TYPE-2, T2020402101-001, STAINLESS STEEL SCREW, TE LOGO
类型-2, T2020402101-001, 不锈钢螺丝, TE LOGO

PANEL CUT OUT FOR INSERTS FOR USE
WITHOUT HOODS/HOUSINGS
不用防护外壳时芯件的安装开孔图

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 16DEC2014 RAGHAVENDRA H M		 TE Connectivity	
DIMENSIONS: mm		CHK 16DEC2014 CHRIS WANG			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 16DEC2014 XU XIANG		PRODUCT SPEC 108-137042	
0 PLC ±-		PRODUCT SPEC		APPLICATION SPEC	
1 PLC ±-		114-137042		WEIGHT	
2 PLC ±-		Customer Drawing		SCALE 1:1	
3 PLC ±-		Customer Drawing		SHEET 1 OF 2	
4 PLC ±-		Customer Drawing		REV B2	
ANGLES ±-		Customer Drawing		RESTRICTED TO	
FINISH		Customer Drawing		SIZE A3	
MATERIAL		Customer Drawing		CAGE CODE 00779	
-		Customer Drawing		DRAWING NO. T2020402101000	
-		Customer Drawing		RESTRICTED TO	

1470-19 (3/13)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
-		SEE SHEET 1	-	-	-

NOTE:
SEE SHEET 1

注释:
见页 1

TYPE-3, T2020402101-002, STAINLESS STEEL SCREW, NO LOGO
类型-3, T2020402101-002, 不锈钢螺丝, 无LOGO

T2020402101-002	HD-040-M	HD-040 MALE INSERT, STAINLESS STEEL SCREW, NO LOGO HD-040 公插, 不锈钢螺丝, 无LOGO	TYPE-3 类型-3
T2020402101-001	HD-040-M	HD-040 MALE INSERT, STAINLESS STEEL SCREW HD-040 公插, 不锈钢螺丝	TYPE-2 类型-2
T2020402101-000	HD-040-M	HD-040 MALE INSERT HD-040 公插	TYPE-1 类型-1
PART NUMBER 料号		PART DESCRIPTION 描述	TYPE 类型

ALL DIMENSIONS ARE SAME AS TYPE 1,
EXCEPT THOSE DEFINED IN THIS TYPE.
除了在本类型中定义的尺寸外, 其它尺寸同类型 1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 16DEC2014 RAGHAVENDRA H M		
DIMENSIONS: mm		CHK 16DEC2014 CHRIS WANG		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 16DEC2014 XU XIANG	NAME HD-040-M	
0 PLC ±-		PRODUCT SPEC 108-137042	SIZE CAGE CODE DRAWING NO RESTRICTED TO	
1 PLC ±-		APPLICATION SPEC 114-137042	A300779 © T2020402101000	
2 PLC ±-		WEIGHT -	SCALE 1:1 SHEET 2 OF 2 REV B2	
3 PLC ±-				
4 PLC ±-				
ANGLES ±-				
MATERIAL -				
FINISH -				
		Customer Drawing		

1470-19 (3/13)