

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A1	ECR-15-010494		14JUL2015	DW	CW
B	ECR-15-013292		24SEP2015	DL	CW
B1	ECR-15-017530		02DEC2015	GY	CW
B2	ECR-16-015492		08NOV2016	QY	CW

M4 SCREW RECOMMENDED  
TIGHTENING TORQUE 1.2Nm  
M4 螺丝, 推荐锁紧力矩 1.2Nm

4X M3 SCREW RECOMMENDED  
TIGHTENING TORQUE 0.5Nm  
4X M3螺丝, 推荐锁紧力矩 0.5Nm

NOTES:

1. TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 250 V  
RATED CURRENT: 10 A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 4 KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
WIRE RANGE: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
CONTACT TYPE: CRIMP CONTACT

2. CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20200X10XX000)

注释:

1. 技术参数:  
绝缘材料: PC  
额定电压: 250V  
额定电流: 10A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 4 KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
接线范围: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
接线类型: 冷压接

2. 端子需要单独订购.  
(订货号参考图面: T20200X10XX000)

TYPE-1, T2020402101-000, TE LOGO  
类型-1, T2020402101-000, TE LOGO

TYPE-2, T2020402101-001, STAINLESS STEEL SCREW, TE LOGO  
类型-2, T2020402101-001, 不锈钢螺丝, TE LOGO

PANEL CUT OUT FOR INSERTS FOR USE  
WITHOUT HOODS/HOUSINGS  
不用防护外壳时芯件的安装开孔图

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN		RAGHAVENDRA H M	
mm		0 PLC	±-	CHK	16DEC2014	TE Connectivity	
		1 PLC	±-	APVD	16DEC2014	NAME	
		2 PLC	±-	PRODUCT SPEC	XU XIANG	HD-040-M	
		3 PLC	±-	APPLICATION SPEC		SIZE	CAGE CODE
		4 PLC	±-	WEIGHT		A3	00779
		ANGLES	±-	Customer Drawing		DRAWING NO	T2020402101000
MATERIAL		FINISH		SCALE	1:1	SHEET	1 OF 2
				REV			B2

1470-19 (3/13)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
-		SEE SHEET 1	-	-	-

NOTE:  
SEE SHEET 1

注释:  
见页 1

TYPE-3, T2020402101-002, STAINLESS STEEL SCREW, NO LOGO  
类型-3, T2020402101-002, 不锈钢螺丝, 无LOGO

T2020402101-002	HD-040-M	HD-040 MALE INSERT, STAINLESS STEEL SCREW, NO LOGO HD-040 公插, 不锈钢螺丝, 无LOGO	TYPE-3 类型-3
T2020402101-001	HD-040-M	HD-040 MALE INSERT, STAINLESS STEEL SCREW HD-040 公插, 不锈钢螺丝	TYPE-2 类型-2
T2020402101-000	HD-040-M	HD-040 MALE INSERT HD-040 公插	TYPE-1 类型-1
PART NUMBER 料号		PART DESCRIPTION 描述	TYPE 类型

ALL DIMENSIONS ARE SAME AS TYPE 1,  
EXCEPT THOSE DEFINED IN THIS TYPE.  
除了在本类型中定义的尺寸外, 其它尺寸同类型 1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 16DEC2014 RAGHAVENDRA H M		
		CHK 16DEC2014 CHRIS WANG		
		APVD 16DEC2014 XU XIANG	NAME HD-040-M	
DIMENSIONS: mm		PRODUCT SPEC 108-137042		SIZE CAGE CODE DRAWING NO RESTRICTED TO A300779 C-T2020402101000 -
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-		APPLICATION SPEC 114-137042		
MATERIAL -		WEIGHT -		SCALE 1:1 SHEET 2 OF 2 REV B2
		Customer Drawing		

1470-19 (3/13)