

Exploded view diagram of the 1000mm long, 100mm high extruded aluminum profile (Type 1000). The diagram shows the profile with various mounting brackets and fasteners. Dimensions include a total length of 22.59 inches [573.9] and a mounting bracket height of 1.62 inches [41.3]. A triangle with the letter 'B' is shown below the profile.



1. SEE CURRENT CATALOG FOR ADDITIONAL PART SUFFIXES TO INDICATE PACKAGE QUANTITY.
2. THE FIBER ROUTING 4-POST RACK BRACKET ALLOWS FOR 5/8" THREADED ROD (NOT INCLUDED) TO BE MOUNTED TO THE TOP OF A PANDUIT 4-POST RACK (CMR4P84).
3. THE FIBER ROUTING 4-POST RACK BRACKET KIT INCLUDES:
 - ONE (1) STRUT METAL FRAMING CHANNEL,
 - TWO (2) SQUARE NUT PEM SELF-CLINCHING ASSEMBLIES,
 - TWO (2) STRUT METAL FRAMING CHANNEL U-WASHERS
 - 7/16" HOLE,
 - TWO (2) 3/8" HELICAL SPRING LOCKWASHERS,
 - TWO (2) 3/8-16x2 1/2" HEX HEAD CAP SCREWS,
 - ONE (1) STRUT METAL FRAMING CHANNEL U-WASHER
 - 1 1/16" HOLE,
 - ONE (1) 5/8" HELICAL SPRING LOCKWASHER,
 - ONE (1) 5/8-11 HEAVY HEX NUT,
 - ONE (1) 5/8-11 CHANNEL NUT WITHOUT SPRING
4. FINISH COLOR: BLACK (EXCEPT FOR HARDWARE).
5. DIMENSIONS IN PARENTHESES ARE IN METRIC.

CAD FILENAME/LAYERS		FR4PRB58.pdf	
		CORP TINLEY PARK, ILLINOIS	
FIBER ROUTING 4-POST RACK BRACKET - 5/8" THREADED ROD (FR4PRB58)  CUSTOMER DRAWING			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ± (.XX) ± .03 (.8) ANGLES ±		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.	
DRAWN BY MSO	MAT'L: STEEL	SCALE NONE	
DATE 5-18-04		DRAWING NO. 38780-10	DWG A SIZE
CHK'D RPA			