Product datasheet Characteristics

9007C66B2S10

Main

Device short name	C
Series name	Heavy duty

Complementary

Line Rated Current	10 A
Body material	Zinc alloy
Contact code designation	A600 R300
Contacts material	Silver alloy (Ag/Ni)
Contact operation	Snap action
Maximum displacement angle	90 °
Specificity of operator	Standard pre-travel First stage : 10° - second stage : 2.5°
Switch actuation	CW and CCW
Torque value	4 lbf.in
Tripping angle	4 °

Environment

ambient air temperature for operation	-20185 °F
product certifications	CE CSA UL listed

Offer Sustainability

Not Green Premium product	Not Green Premium product	
Will not be Compliant	Will not be Compliant	
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold	
Available	Available	
Need no specific recycling operations	Need no specific recycling operations	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the State Diisononyl phthalate (DINP), which is known to the State of California to cause of California to cause cancer, and cancer, and		
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm.		

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period

18 months

