




SIMPLEX FIBER OPTIC SC/APC TO SC/APC PATCH CORD							
PANDUIT PART NO.	CABLE				SC/APC CONNECTOR		
	RATING	FIBER TYPE	COUNT	COLOR	MAX. IL	RL	COLOR
F9F3A-3AM*	RISER (OFNR)	9/125um OS1	SIMPLEX 1.6mm	YELLOW	0.50dB	65dB	GREEN
F9S3A-3AM*	RISER (OFNR)	9/125um OS1	SIMPLEX 3.0mm	YELLOW	0.50dB	65dB	GREEN

* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

											SIMPLEX FIBER OPTIC PATCH CORD SC/APC TO SC/APC CONFIGURATION CUSTOMER DRAWING			
												 TINLEY PARK, ILL 60477		
											 THIRD ANGLE PROJECTION	ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (.X) (.XXX) ± .010 (.0.3) (.XX) ± .03 (.0.8) ANGLES	DRAWING FILENAME M02779CN_DC_00A.prt SCALE NONE	
											DRAWN BY MC	REVIEW DRAWING NUMBERS	PART NO. SEE TABLE	
R	06-14-07	MC		RELEASED TO PRODUCTION	02779-43						DATE 06-08-07		DRAWING NO. 02779-43 (SHT. 2 of 2)	SIZE A
REV	DATE	BY	CHK	DESCRIPTION	ECN	-	R	CUST	SUP	OTH	CHK'D			

