



### Main

|                              |                      |
|------------------------------|----------------------|
| Range of product             | 9050JCK              |
| Product or component type    | Timer                |
| Time delay type              | Repeat cycle         |
| Time delay range             | 0.1...10 min         |
| [Uc] control circuit voltage | 110 V DC<br>120 V AC |

### Complementary

|                                 |                      |
|---------------------------------|----------------------|
| Hold-in power consumption in VA | 2 VA                 |
| Line Rated Current              | 10 A                 |
| Switch function                 | DPDT                 |
| Contacts type and composition   | 2 NO + 2 NC          |
| Contacts material               | Silver nickel        |
| Maximum switching voltage       | 240 V AC             |
| Mounting support                | Socket               |
| Pin number                      | 8                    |
| Shape of pin                    | Tubular              |
| Product compatibility           | 8501NR51<br>8501NR52 |

### Environment

|                                       |  |
|---------------------------------------|--|
| product certifications                | CE<br>RoHS<br>UL listed<br>UL recognized |
| ambient air temperature for operation | -18...150 °F                             |
| height                                | 2.4 in (61 mm)                           |
| width                                 | 1.69 in (43 mm)                          |
| depth                                 | 4.09 in (104 mm)                         |

### Offer Sustainability

|   |   |
|---|---|
| Green Premium product   | Green Premium product   |
| Compliant - since 0627 - Schneider Electric declaration of conformity | Compliant - since 0627 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold                     | Reference not containing SVHC above the threshold                     |
| Available   | Available   |
| Available   | Available   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|