

Technical drawing of a mechanical part with dimensions: 1.6, 3.5, 1.9, Ø9.9, and 13.0.

The diagram shows the bottom of a 1000mAh battery with two main markings: "Silk Screen Marking" pointing to the central area and "Date Code Marking '8 B'" pointing to the bottom edge. Below the diagram, a legend indicates: Year 10=2010, B=Feb, and Month 8.

Specifications			Notes	Revision History					
Description	Value	Unit		Version	Description		Date	Approved	
Shape	Oval		1) All dimensions are in mm unless otherwise noted 2) All parts meet RoHS	1	Released from Engineering		2/5/2014	J.S	
Resonant Frequency	850	(Hz)							
Frequency Range	200 ~ 10,000	(Hz)							
SPL @ 10cm	89	(dBA)							
Impedance	8	(Ohm)							
Cone Material	Mylar								
Nominal Power	0.8	(W)							
Max Power	1	(W)							
Mount Type	Flush Mount								
Operating Temperature	- 30 ~ + 70	°C							
Storage Temperature	- 30 ~ + 70	°C		Drawn by	Date	Checked by	Date	Approved by	Date
Weight	1.3	(g)		G.W.	10/31/2013	C.E.	10/21/2013	J.S	2/5/2014
			DB UNLIMITED	Dynamic Speaker			SM180808-1		