




4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

DY

P

LTR



DESCRIPTION

DATE

DWN

APVD

SEE SHEET 1

SECTION B-B
(WITH & W/O PART)0.50±0.05
(BEFORE FORMING)

SEE DETAIL X

CUSTOMER DE-REEL DIRECTION

50.0 REF
46.0 REFWIND COVER TAPE
AROUND OUTER
PERIPHERY 1 TURN

SECTION C-C

165°~180°

LEADER LENGTH
450mm
(W/O CHARGE)

WITH PRODUCT CHARGE

TRAILER LENGTH
400mm
(W/O CHARGE)Ø330
REF

Ø100.0 REF

NOTES:

- ALL DIMENSIONS IN MM UNLESS OTHERWISE STATED
- MATERIAL: PS CLEAR, 0.5±0.05mm THICKNESS (BEFORE FORMING)
- DELIVER IN PLASTIC REEL: 375 POCKETS/REEL
(300 COMPONENTS/REEL)

PEELING STRENGTH: 0.2N TO 0.7N
PEELING ANGLE: 165° TO 180°
PEELING SPEED: 300mm/MINUTE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN KW YAP 12MAY2008

CHK SF LEONG 02JUL2013

APVD SF LEONG 02JUL2013

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

-

CUSTOMER DRAWING

TE

TE Connectivity

NAME

ASSEMBLY SLIMLINE SATA PLUG 7P+6P
VERTICAL, THRU-HOLE

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-1735574

SCALE 4:1

SHEET 3

OF 3

REV A3