

<h3>0291</h3> <p>0291-0-15-XX-16-XX-10-0 Hex press-fit in .067 plated thru hole</p>	<h3>0293</h3> <p>0293-0-15-XX-16-XX-10-0 Press-fit in .067 mounting hole</p>	<h3>0287</h3> <p>0287-0-15-XX-16-XX-10-0 Solder mount in .065 min. mounting hole Also available on 8mm wide carrier tape: 3,250 parts per 13" reel. Order as: 0287-0-57-XX-16-XX-10-0</p>	<h3>0285</h3> <p>0285-0-15-XX-16-XX-10-0 Solder mount in .065 min. mounting hole</p>
--	---	--	---

<h3>0284</h3> <p>0284-0-15-XX-16-XX-10-0 Solder mount in .070 min. mounting hole</p>	<h3>8114</h3> <p>8114-0-15-XX-16-XX-04-0 Press-fit from underside of pc board into .065 mounting hole</p>	<h3>0407</h3> <p>0407-0-15-XX-16-XX-04-0 Press-fit in .066 mounting hole</p>	<h3>0415</h3> <p>0415-0-15-XX-16-XX-10-0 Solder mount in .063 min. mounting hole Also available on 24mm wide carrier tape: 1,500 parts per 13" reel. Order as: 0415-0-57-XX-16-XX-10-0</p>
---	--	---	---

<h3>0303</h3> <p>0303-0-19-XX-16-XX-10-0 Press-fit in .067 mounting hole Wire Crimp Termination. Accepts wire sizes 26 AWG Max. / 30 AWG Min.</p>	<h3>0306</h3> <p>0306-0-19-XX-16-XX-10-0 Wire Crimp Termination. Accepts wire sizes 20 AWG Max. / 24 AWG Min.</p>	<h3>0273</h3> <p>0273-0-15-XX-16-XX-10-0 Press-fit in .078 mounting hole</p>	<h3>7520</h3> <p>7520-0-15-XX-16-XX-10-0 Press-fit in .066 mounting hole</p>
--	--	---	---

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <ul style="list-style-type: none"> 01 200μ" TIN/LEAD OVER NICKEL ◇ 80 200μ" TIN OVER NICKEL (RoHS) ◇ 15 10μ" GOLD OVER NICKEL (RoHS) <p>SPECIFY CONTACT FINISH:</p> <ul style="list-style-type: none"> 01 200μ" TIN/LEAD OVER NICKEL ◇ 80 200μ" TIN OVER NICKEL (RoHS) ◇ 27 30μ" GOLD OVER NICKEL (RoHS) <p style="text-align: center;">CONTACT</p> <p>#16 CONTACT (DATA ON PAGE 222)</p>
--	--