




0970 PSL 112



Profibus I/O Modules with 8-Digital Outputs

8 OUT

Profibus-DP device with 8 digital outputs to connect standard actuators, combined M12 socket, rotary switches for addressing, M12 bus connection, M23 power supply.



Bit Assignment

Bit	7	6	5	4	3	2	1	0
M12 Output								
Byte 0	8	7	6	5	4	3	2	1
Diagnostic								
DIA-Byte	-	UVA	ASC	-	-	-	-	-

UVA: Undervoltage actuator
ASC: Actuator short-circuit

Diagnostic Indication

LED	Indication	Condition
1...8 A	yellow	channel status
1...8	red	actuator short-circuit
Us	green	actuator supply active
Ul	green	module electronic supply active
BF	red	bus error
DIA	red	module diagnostics (sensor short-circuit / sensor overload)

Pin Assignment

Bus connection M12	Power supply M23	Input M12	
<p>1 = +5 V¹ 2 = Line A 3 = GND (0 V)¹ 4 = Line B 5 = earth</p>	<p>1 = Earth 2 = +24 V² 3 = GND (0 V)² 4 = +24 V³ 5 = GND (0 V)³ 6 = n.c.</p>	<p>1 = n.c. 2 = n.c. 3 = GND (0 V) 4 = OUT 5 = Earth</p>	<p>1 = internal signals 2 = actuators 3 = system</p>



Be Certain with Belden

Profibus I/O Modules with 8-Digital Outputs

0970 PSL 112

Technical Data

Environmental

Degree of protection IP 67
 Operating temperature range -0°C (+32°F) to +60°C (+140°F)

Mechanical

Weight 535 g
 Housing material PUR

Bus system

Profibus
 ID number 044D hex
 GSD file Lum_044D.gsd
 Transmission rate max. 12 MBaud
 Address range 1–126 dec
 Rotary address switches 1–99 dec
 Default address 99 dec

Output power supply

Us
 Rated voltage 24 V DC
 Voltage range 19–30 V DC
 Potential separation present
 Reverse polarity protection yes/antiparallel diode
 Indication LED green

Outputs

Type 2 A acc. to IEC 61131-2
 Rated output current 2 A per channel
 Short circuit-proof yes
 Max. output current 15 A per module
 Overload-proof yes
 Number of digital channels 8
 Channel type N.O. p-switching
 Channel status indicator LED yellow per channel
 Diagnostic indication LED red per channel

Included in delivery/accessories

Dust covers M12 2 pieces
 Attachable labels 10 pieces

Part Number

0970 PSL 112



The application of these products in harsh environments should always be checked before use.
 Specifications subject to alteration.