## RAFIX 22 FSR - Keylock switch, latching, 1 x 90°, L shape

## 1.30.285.221/0100





General information	
Color of front ring	black
Form of collar	round
Dimensions	
Dimensions of collar	ø 31.3 mm
Overall height	45.1 mm
Mounting hole	 22.3 mm
Key grid	35 x 35 mm
Mechanical design	
Mounting	ring nut
Contact function	latching
Illuminability	no
Wafers	5
Number of locking types	18
Lock type	001
Main key	on request
Rotating angle	1 x 90°, L shape
Key removal position	0+1
Torque for nut ring	<u>1.2 Nm</u>
Mechanical characteristics	
Torque max.	1.3 Nm
Other specifications	
Degree of protection from front side	IP65 (DIN EN 60529)
Ambient temp. operating min.	-40 °C
Ambient temp. operating max.	+85 °C
Storage temperature min.	-40 °C
Storage temperature max.	+85 °C
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Salt spray	IEC 600 68-2-11
ROHS compliant	yes
REACH compliant	yes

Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.



## Panel cut-out to IEC 60947-5-1







Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.