


# Model 3269 Adapter – BNC Female To Miniature Double Banana Plug



## **FEATURES:**

 Allows a BNC male to be used with equipment having .5" (12,7) spaced miniature .104" (2,4) dia. banana jacks

• Excellent for adapting test equipment to BNC coaxial cables

## **MATERIALS:**

Upper Conn: BNC Female.
Finish: Tarnish Resistant
Center Contact: Gold plated

Insulation: ABS molded to BNC male and Banana Plug

Color: Black

Marking: "POMONA ELECTRONICS CALIF. 3269"

Lower Conn: Miniature Double Banana Plug Material: Spring, Beryllium Copper

> Plug Body: Brass Finish: Gold plated

## **RATINGS:**

Operating Temperature: +50° C. (+122° F.) Max.

Operating Voltage: Hand-Held Testing: 30VAC/60VDC Max.

Hands Free Testing in controlled voltage environments: 500 VRMS Max.

#### **ORDERING INFORMATION:** Model 3269

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (,51 mm),  $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060