

Cable gland - G-ESS-M63-L66L-NTES-S - 1411086

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Nickel-plated brass, Application: Ex, External cable diameter 47.2 mm ... 56 mm, Shielding: No, Connecting thread: M63, Color: silver

Product Features



Key commercial data

Packing unit	1 pc
Minimum order quantity	2 pc
Custom tariff number	74199990
Country of origin	United Kingdom

Technical data

Dimensions

Length	45 mm
Length without connecting thread	30 mm
Connecting thread diameter	63 mm
Wrench size, union nut	75 mm
Wrench size, support	75 mm
Hexagon angular dimension GRP	82.5 mm
Length of the connecting thread	15 mm
External cable diameter	47.2 mm ... 56 mm

Ambient conditions

Degree of protection	IP66 (in the case of feed-through holes, a sealing ring should also be installed in order to maintain the degree of protection (e.g., item 1411283).)
----------------------	---

Cable gland - G-ESS-M63-L66L-NTES-S - 1411086

Technical data

Ambient conditions

	IP67 (in the case of feed-through holes, a sealing ring should also be installed in order to maintain the degree of protection (e.g., item 1411283).)
	IP68 (in the case of feed-through holes, a sealing ring should also be installed in order to maintain the degree of protection (e.g., item 1411283).)
Ambient temperature (operation)	-60 °C ... 130 °C

General

Cable gland material	Nickel-plated brass
Seal material	Thermoplastic elastomers
O-ring material	Viton
Thread type on connection side	M63
Color	silver
Standards/specifications	EN 60079-0, -1, -7, -15, -31
	IEC 60079-0, -1, -7, -15, -31
	EN 50262
	BS 6121: Part 1:1989
	IEC 62444
ATEX	Sira 13ATEX1068X
	Sira 13ATEX4074X
	Ex II 2/3G, II 1D, Ex d IIC Gb, Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da, Ex IM2 Ex d I Mb, Ex e I Mb
IECEx	IECEx SIR 13.0023X
	Ex d IIC Gb, Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da, Ex d I Mb, Ex e I Mb

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Drawings

Cable gland - G-ESS-M63-L66L-NTES-S - 1411086

Dimensional drawing

