



## Main

Range of product	Magelis iPC
Product or component type	External power supply module
Accessory / separate part category	Electrical accessory

## Complementary

Accessory / separate part destination	Magelis HMIPSP Magelis HMIPSO Magelis HMIDAD
Input voltage	90...260 V AC at 47...63 Hz
Input current	1600 mA at 100 V AC
Output voltage	24 V DC
Line Rated Current	2.62 A
Inrush current	70 A at 230 V AC

## Environment

ambient air temperature for operation	0...70 °C
ambient air temperature for storage	-40...185 °F (-40...85 °C)
relative humidity	0...95 % non-condensing
product certifications	CE CULus UL 60950 CSA 60950

## Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1604 - Schneider Electric declaration of conformity	Compliant - since 1604 - Schneider Electric declaration of conformity
WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.