



Main

| | |
|------------------------------------|--|
| Product or component type | Cover |
| Accessory / separate part category | Cabling accessories |
| Range compatibility | Spacial CRN Spacial S3D Thalassa PLA Thalassa PLS Thalassa PLM |
| Mounting support | Cable duct width= 60 mm |
| Quantity per set | Set of 8 |

Complementary

| | |
|----------------|--------------------------|
| Colour | Blue RAL 5000 |
| Length | 78.74 in (2000 mm) |
| Width | 2.36 in (60 mm) |
| Material | PVC (polyvinyl chloride) |
| Product weight | 0.95 lb(US) (0.43 kg) |

Environment

| | |
|---------------------------------------|--|
| ambient air temperature for operation | 23...140 °F (-5...60 °C) |
| flame retardance | VO conforming to UL 94 |
| fire resistance | 1760 °F (960 °C) conforming to IEC 60695-2-1/1 |
| standards | DIN 43659 VDE 0506 VDE 0660 |

Offer Sustainability

| | |
|--|--|
| WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
|--|--|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.