## Product data sheet Characteristics

# SMT3000RM2UNC APC Smart-UPS 3000VA LCD RM 2U 120V with **Network Card**



#### Overview

Model Name	APC Smart-UPS 3000VA LCD RM 2U 120V with Network Card	
Includes	CD with software	
Standard Lead Time	Usually in Stock	
Product Distribution	Canada	

### Output

Model Name	APC Smart-UPS 3000VA LCD RM 2U 120V with Network Card	
Includes	CD with software	
Standard Lead Time	Usually in Stock	
Product Distribution	Canada	
Output		
Output Power Capacity	2700 Watts / 2880 VA	
Max Configurable Power (Watts)	2700 Watts / 2880 VA	
Nominal Output Voltage	120V	
Output Voltage Distortion	Less than 5%	
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz	
Output Frequency (sync to mains)	Line Interactive	
Waveform Type	Sine wave	
Output Connections	(2) NEMA 5-20R (Battery Backup)	
Input Nominal Input Voltage	120V	
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)	
Input Connections	NEMA L5-30P	
Cord Length	2.44 meters	
Input voltage range for main operations	82 - 144 V	
Input voltage adjustable range for mains operation	75 - 154V	
Batteries & Runtime		
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte: leakproof	
Typical recharge time	3 hour(s)	
Replacement Battery	RBC43	
RBC Quantity	1	

#### Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NEMA L5-30P
Cord Length	2.44 meters
Input voltage range for main operations	82 - 144 V
Input voltage adjustable range for mains operation	75 - 154V

#### **Batteries & Runtime**

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3 hour(s)
Replacement Battery	RBC43
RBC Quantity	1

### Communications & Management

Interface Port(s)	RJ-45 Serial
Pre-Installed SmartSlot™ Cards	AP9631
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

### Surge Protection and Filtering

|--|

### Physical

Maximum Height	86.0 mm	
Maximum Width	480.0 mm	
Maximum Depth	683.0 mm	
Rack Height	2 U	
Net Weight	44.28 kg	
Shipping Weight	51.68 kg	
Shipping Height	254.0 mm	
Shipping Width	600.0 mm	
Shipping Depth	980.0 mm	
Color	Black	

### Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	55.000 dB
Online Thermal Dissipation	348.000 BTU/hr

### Conformance

Approvals	CSA
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery
Equipment protection policy	Lifetime: \$150000

### Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant