



PA66 NATURAL MATERIAL
ACC TO SPEC IEC 60335-1
GWT 750° WITHOUT FLAME

MOISTURISED PRODUCT FOR
SMALL WIRE APPLICATIONS

ONLY FOR USE WITH POST PLATED
OR WASHED CONTACTS

4

RIB IS EXTEND TO FRONT OF HOUSING
FOR BRAZIL PRODUCTION

5

USING EQUIVALENT ALTERNATE MATERIAL

OBSOLETE		8-154719-6	As Drg	UL 94 V0	PA 66	Orange
		8-154719-5	As Drg	UL 94 V2	PA 6/6 or Equivalent	Natural
OBSOLETE		8-154719-4	As Drg	UL 94 V0	PA 66	Natural
		8-154719-3	As Drg.	UL 94 V0	PA 66/6	Terracotta
OBSOLETE		8-154719-1	As Drg.	UL 94 V2	PA 6/6 or Equivalent	Black
		8-154719-0	As drg.	UL 94 V0	PA 6/6 or Equivalent	Clear
		7-154719-0	AE	UL 94 V0	PA 66	Orange (Ral 2000)
		6-154719-6	AB	UL 94 V2	PBT	Black
		5-154719-0	AB	UL 94 V0	PPE+PS	Orange
		4-154719-0	AA	UL 94 V0	PA 66	(Bk-59 Black)
		2-154719-0	AA	UL 94 V0	PPE+PS	Red
		1-154719-1	As Drg.	UL 94 V0	PA 6/6 or Equivalent	Natural
		1-154719-0	AE	UL 94 V0	PA 6/6 or Equivalent	Natural
		154719-9	As Drg.	UL 94 V2	PA 6/6 or Equivalent	Brown
		154719-6	As Drg.	UL 94 V2	PA 6/6 or Equivalent	Blue
		154719-5	As Drg.	UL 94 V2	PA 6/6 or Equivalent	Green
		154719-4	As Drg.	UL 94 V2	PA 6/6 or Equivalent	Yellow
		154719-2	As Drg.	UL 94 V2	PA 6/6 or Equivalent	Red
		154719-1	As Drg.	UL 94 V2	PA 6/6 or Equivalent	Natural
		154719	As. Drg.	UL 94 V2	PA 6/6 or Equivalent	Black
	Notes	Part Number	Part Revision	Flammability Rating	Material	Colour

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	09MAY2002
A	1 DEKEN

A. J. BERN	
CHK	09MAY2002

S. CLAPPISON
APR 20 00 MAY 2002

S. CLAPPISON

PRODUCT SPEC

108-3252

APPLICATION SPEC
114 2152

114-2153
WEIGHT

WEIGHT	0.5g
--------	------

Customer Drawing



TE Connectivity

NAME	POSITIVE LOCK RECEPTACLE INSULATOR
------	---------------------------------------

—

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
------	-----------	------------	---------------

LA 200330 © 154710

AZ00779	G=154779	-
---------	----------	---

SCALE 5.1 SHEET OF REV AV5

1471-9 (3/11)