AC Filter 3-Stage, Very High Broad Band Attenuation



The same image is used for FMW-200

See below:

Approvals and Compliances

Description

- Line-filter in standard version
- 3 stages
- very high attenuation, broadband

Characteristics

- Designed for highest demands
- High attenuation at maximum resp. asymmetric load independent from the line impedance
- For standard and industrial applications
- Suitable for use in equipment according to IEC/UL 62368-1

References

Alternative: Standard version

Weblinks

pdf data sheet, html datasheet, General Product Information, Approvals, Distributor-Stock-Check, Detailed request for product, Microsite

Technical Data	
Ratings IEC	4 - 30 A @ Ta 40 °C / 250 VAC; 50 Hz
Ratings UL/CSA	4 - 30 A @ Ta 40 °C / 125 VAC; 60 Hz
Leakage Current	industrial < 1.5 mA (250 V / 60 Hz)
Dielectric Strength	> 1.7 kVDC between L-N
	> 2.7 kVDC between L/N-PE
	Test voltage (2 sec)
Allowable Operation Tempe-	-25 °C to 100 °C
rature	
Climatic Category	25/100/21 acc. to IEC 60068-1
Protection Class	Suitable for appliances with protection
	class I acc. to IEC 61140
Terminal	Screw
Material: Housing	Metal

Line Filter	Industrial version, IEC 60939, UL 1283, CSA C22.2 no. 8
	Technical Details
MTBF	> 200'000 h acc. to MIL-HB-217 F

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: FMW-150 (200)

Approval Logo	Certificates	Certification Body	Description
10	VDE Approvals	VDE	Certificate Number: 40004673
c FU °us	UL Approvals	UL	UL File Number: E72928

Product standards

Product standards that are referenced

Standard	Description
D IEC 60939	Passive filters for suppressing electromagnetic interference
D UL 1283	Electromagnetic interference filters
CSA C22.2 no. 8	Electromagnetic interference (EMI) filters
	D IEC 60939 D UL 1283

Application standards

Application standards where the product can be used

Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 62368-1	IEC 62368-1 includes the basic requirements for safety of audio, video, information technology and office equipment.


Compliances


The product complies with following Guide Lines


Identification	Details	Initiator	Description
C€	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
©	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.


Dimension [mm]

Case 43 Case 22










- 1) Line
- 2) Load
- 3) I/O connections torque 0.6...0.8 Nm

- 1) Line
- 2) Load
- 3) I/O connections torque 1.5...1.8 Nm

- - - - 50Ω differential mode _____ 50Ω common mode

Diagrams

Standard version




10 A


1) Line 2) Load

Attenuation Loss

Industrial version

4 A





All Variants

Rated Cur- rent [A]	Filter-Type	Leakage Cur- rent [mA]	L1 [mH]	L2 [µ H]	L3 [µH]	Cx [nF]	Cy1 [nF]	Cy2 [nF]	R [MΩ]	Clamps [mm2]	Weight [kg]	Housings	Order Number
4	Industrial version	3.5	2 x 20	2 x 30	3	220	33	2.2	0.5	4	1600 g	43	5500.2048
10	Industrial version	1.5	2 x 5	2 x 30	3	220	15	-	0.5	4	-	43	5500.2049
30	Industrial version	1.5	2 x 4	2 x17	3	220	15	-	0.5	6	3220 g	22	5500.2050

30 A

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit

1 Pcs