



Quality Products. Service Excellence.

## 15 Amp Heavy Duty Surge Strip 1584-S Series



### Features

- Built to meet the rugged requirements of commercial and industrial use.
- All metal housing - tough extruded aluminum case with a black powder paint coated steel cover.
- Heavy duty NEMA 5-15R receptacles.
- Mounting feet (with keyhole slots) allow temporary work station mounting if desired.
- On-Off switch is rocker type with pilot light (on units with on-off switch). A red pilot light is used to indicate power on (on units with no switch).
- [Click here for our non-surge protected version.](#)

### Specifications

- Heavy duty 14 gauge wire cord - 14/3 SJT type for extreme temperature ranges and integral molded plug.
- Plug types available are NEMA 5-15P straight blade or NEMA L5-15P locking type (see table below).
- Includes 15 amp, 125 volt resettable circuit breaker to prevent accidental line overload.
- Includes our surge module:
  - Max Energy (Joules) is 1080 J.
  - 25000 Amp rated MOV's for a total of 75,000 Amps of single pulse transient current.
  - Voltage Protection Rating (Vpr) of 500V, in all 3 modes (L-N, L-G, N-G).
  - Nominal Discharge Current (In) of 5kA.
  - Voltage suppression at the outlet guards against transients from equipment on the outlet strip.
  - Green indicator light confirms surge module is active.
  - Internal protection will disconnect the surge module at the end of it's useful life (and extinguish the green light) but will maintain power to the load, now unprotected.
- cULus Listed to UL 1449 & C22.2 No. 269.3-17, for Surge Protective Devices – Type 3.
- cULus Listed to UL 1363 & C22.2 No. 308-18, for Relocatable Power Taps & Multi Outlet Assemblies.



### Accessories

- Rack Cabinet Vertical Mount Adaptor

| Illuminated On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions |       |        | Outlet Qty | Outlet NEMA Type | Outlet Rotated | Cord Length (ft) | Plug Type | Plug NEMA Type |
|------------------------------------|---------------------------------|--------------------|-------|--------|------------|------------------|----------------|------------------|-----------|----------------|
|                                    |                                 | Height             | Width | Length |            |                  |                |                  |           |                |
| 1584H6A1S                          | 1584T6A1S                       | 2.33               | 2.12  | 16.51  | 6          | 5-15R            | No             | 6                | Straight  | 5-15P          |
| 1584H6A1SRA                        | 1584T6A1SRA                     | 2.33               | 2.12  | 16.51  | 6          | 5-15R            | Yes            | 6                | Straight  | 5-15P          |
| 1584H6B1S                          | 1584T6B1S                       | 2.33               | 2.12  | 16.51  | 6          | 5-15R            | No             | 15               | Straight  | 5-15P          |
| 1584H6B1SRA                        | 1584T6B1SRA                     | 2.33               | 2.12  | 16.51  | 6          | 5-15R            | Yes            | 15               | Straight  | 5-15P          |

## Replacement Mounting Foot (One Foot)

Part No.

1584MF

*Data subject to change without notice*

© 2020. Hammond Manufacturing Ltd. All rights reserved.