

3719-1**4.5" x 6.5"****Circuit Pattern:**
Contacts:Contacts Only
36/72 @ .100" Ctrs,
Ni/Gold**Width/Thick:**

6.50"/.062"

Height:

4.50"

16-Pin DIP Capacity:

50

Material:

CEM-1

Wire-Wrap Terminals:

T44, T46, T49, T68

Wire-Wrap Socket Pins:

R32

Solder Connector:

R636-2

Extender:

3690-4

Rec. Card Cage:

Series 13


Wire-Wrap Connector:

R636-1

Hole Diameter:

.042"

- Unrestricted component placement over entire board surface
- Layout paper and instructions included
- Row and column legends provided

**3719-6****4.5" x 6.5"****Circuit Pattern:**
Contacts:Pad-Per-Hole
36/72 @ .100" Ctrs,
Ni/Gold**Width/Thick:**

6.50"/.062"

Height:

4.50"

16-Pin DIP Capacity:

40

Material:

FR4 Epoxy Glass

Wire-Wrap Terminals:

T44, T46, T49, T68

Wire-Wrap Socket Pins:

R32

Solder Connector:

R636-2

Extender:

3690-4

Rec. Card Cage:

Series 13


Wire-Wrap Connector:

R644-1

Hole Diameter:

.042"

- 0.080" diameter, isolated solder pad around holes, plated-thru holes
- Low resistance, etched peripheral bus pattern
- Pad and bus surfaces solder-coated for user convenience
- Convenient, easy-to-read hole marking legend on board surface
- Layout paper and instructions included

**4066-4****4.5" x****6.5"****Circuit Pattern:**
Contacts:Ground Plane/
Interleaved Buses
36/72 @ .100" Ctrs,
Ni/Gold**Width/Thick:**

6.50"/.062"

Height:

4.50"

16-Pin DIP Capacity:

34

Material:

CEM-1

Wire-Wrap Terminals:

T44, T46, T49, T68

Wire-Wrap Socket Pins:

R32

Solder Connector:

R636-2

Extender:

3690-4

Rec. Card Cage:

Series 13


Wire-Wrap Connector:

R636-1

Hole Diameter:

.042"

- Overall ground plane on wiring side; etched, interleaved zig-zag bus pattern on component side provides three bus lines for ECL circuitry
- 0.085" etched clearance area around each hole on ground plane side
- Bus and plane surfaces solder-coated for user convenience
- Layout paper and instructions included

**3719-4****4.5" x 9.6"****Circuit Pattern:**
Contacts:Contacts Only
36/72 @ .100" Ctrs,
Ni/Gold**Width/Thick:**

9.60"/0.62"

Height:

4.50"

16-Pin DIP Capacity:

90

Material:

CEM-1

Wire-Wrap Terminals:

T44, T46, T49, T68

Wire-Wrap Socket Pins:

R32

Solder Connector:

R636-2

Extender:

3690-2

Rec. Card Cage:

Series 14

Wire-Wrap Connector:

R636-1

Hole Diameter:

.042"

- Unrestricted component placement over entire board surface
- Row and column legends provided
- Layout paper and instructions included

