



SPECIFICATIONS


- 1. CASE:
22 GA. (.030) CRS, TIN PLATED
- 2. RATED CURRENT:
20A
- 3. RATED VOLTAGE:
50VDC
- 4. TEST VOLTAGE:
LINE TO GROUND: 150VDC



INSERTION LOSS (50Ω TYPICAL)

	.02 MHz	.15 MHz	.50 MHz	1.5 MHz	5.0 MHz	50 MHz
L/L	35 db	55 db	65 db	65 db	65 db	60 db
L/G	30 db	50 db	60 db	60 db	60 db	50 db

SCHEMATIC



NEXT ASSY	USED ON
APPLICATION	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± .XX ±.030 ± .XXX ±.010	CONTRACT NO.		FILTER CONCEPTS INC.			
	APPROVALS		DATE		APPLICATION DRAWING	
	DRAWN		DATE		D2L20 FS01 FILTER	
	CHECKED		DATE		SIZE	CODE IDENT NO.
	DANNIEL VUONG		10-02-03		B	7004-1
MATERIAL					SCALE	2/3
FINISH					SHEET 1 OF 1	