

## MKDSN 2,5/ 9-B-5,08 MC NZ B3-4 - 1709120

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



PCB terminal block, nominal current: 16 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 9, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: multi-color

The figure shows a 2-pos. version of the product

### Your advantages

- ✓ Allows connection of two conductors
- Extremely small design for the respective conductor cross section
- Integrated protective guide prevents incorrect insertion of the conductor underneath the tension sleeve
- The latching on the side enables various numbers of positions to be combined



## **Key Commercial Data**

Packing unit	50 pc
GTIN	4 055626 064239
GTIN	4055626064239

#### Technical data

#### **Environmental Product Compliance**

REACh SVHC	Lead 7439-92-1		
China RoHS	Environmentally Friendly Use Period = 50		
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"		

## Approvals

#### Approvals



# MKDSN 2,5/ 9-B-5,08 MC NZ B3-4 - 1709120

Approvals			
Approvals			
EAC			
Ex Approvals			
Approval details			
EAC	ERC		B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 3 41200

http://www.phoenixcontact.com