








rev	ecn no	dr	date
A	V05-0321	TAB	04/08/05
B	V05-1009	LP	11/7/05
C	V06-0239	LP	3/27/06
D	V06-0558	LP	2006/06/21
E	V07-0440	LP	2007-07-09
F	V09-0071	PK	2009-02-24



spec ref -				dr Bill Lin2010/02/02		projection 	mm 	size A4	scale 1:1		
tolerance std ASME Y14.5 -TOLERANCES UNLESS OTHERWISE SPECIFIED				eng Nickor Zuo2011/06/13				ecn no ELX-DG-003943-1			
				chr Alex Cao2011/06/24				rel level Released			
				appr Pei-Ming Zheng2011/06/27		product family GIG-Array					
surface ✓ -	linear	0.X	±0.30		title	GIG-Array 13mm PLUG ASSY. 200 SIG. POS.	dwg no	10055142		rev	G
		0.XX	±0.10								
		0.XXX	±0.05								
		angular	0°	±2°	www.fci.com	cat. no.	Product - Customer Drw			sheet 1 of 5	



Copyright FCI.








spec ref -				dr Bill Lin		2010/02/02		projection		mm		size A4		scale 1:1							
tolerance std ASME Y14.5 -		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng Nickor Zuo		2011/06/13						ecn no ELX-DG-003943-1							
						chr Alex Cao		2011/06/24						rel level Released							
						appr Pei-Ming Zheng		2011/06/27						product family GIG-Array							
surface ✓		linear		0.X ±0.30		0.XX ±0.10		0.XXX ±0.05				title GIG-Array		dwg no 10055142		rev G					
-		angular		0° ±2°		www.fci.com		cat. no.		Product - Customer Drw				sheet 2 of 5							

PrintE File - REV C - 2009-06-09





Copyright FCI.






spec ref -				dr Bill Lin 2010/02/02		projection 	mm 	size A4	scale 1:1
tolerance std ASME Y14.5 -	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng Nickor Zuo 2011/06/13				ecn no ELX-DG-003943-1	
				chr Alex Cao 2011/06/24				rel level Released	
				appr Pei-Ming Zheng 2011/06/27					
surface 	linear	0.X	±0.30		title GIG-Array 13mm PLUG ASSY. 200 SIG. POS.			dwg no 10055142	rev G
		0.XX	±0.10						
		0.XXX	±0.05						
	-	angular	0°						

FLAT AREA
FOR OPTIONAL
PICK-UP CAP



DIM. "A"	RECPT. ASSY. P/N
28	55741
18	55740

spec ref -				dr	Bill Lin	2010/02/02	projection 	mm 	size	A4	scale	1:1	
tolerance std ASME Y14.5 -	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Nickor Zuo	2011/06/13			ecn no	ELX-DG-003943-1			
				chr	Alex Cao	2011/06/24							
				appr	Pei-Ming Zheng	2011/06/27							
product family							GIG-Array		rel level			Released	
surface ✓ -	linear	0.X	±0.30		title	GIG-Array 13mm PLUG ASSY. 200 SIG. POS.			dwg no	10055142		rev	G
		0.XX	±0.10										
		0.XXX	±0.05										
	angular	0°	±2°	www.fci.com	cat. no.	Product - Customer Drw				sheet 4 of 5			



Copyright FCI.




PRODUCT NUMBER	SOLDER BALL COMPOSITION	CONTACT PLATING PERFORMANCE LEVEL
10055142-001	STANDARD (EUTECTIC)	PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12-192, INCLUDING TELCORDIA CENTRAL OFFICE Au over Ni
10055142-001LF	LEADFREE	
10055142-201	STANDARD (EUTECTIC)	
10055142-201LF	LEADFREE	

NOTES:

① MAT'L:

HOUSING: LCP
CONTACT: COPPER ALLOY
PLATING (CONTACT): Au OVER Ni.
UL RATING: 94 V-0
SOLDER BALL: (SEE TABLE) EUTECTIC
SnPb OR LEADFREE 95.5 Sn/4Ag/0.5Cu

② SOLDER BALLS WILL NOT BE PERFECT
SPHERICAL SHAPE DUE TO REFLOW ATTACHMENT.③ MATED HEIGHT EFFECTED BY CUSTOMERS'
PCB PAD SIZE, PLATING, SOLDER REFLOW
PROFILE & SOLDER PASTE.④ CONTACTS IN ROWS A,C,E,G,J,K,M,P,R AND T
ARE SINGLE BEAM CONTACTS,
TYPICALLY USED AS GROUND PINS.
(NOTE: CONTACTS IN ROWS J & K ARE
TIED TOGETHER [COMMONED])⑤ CONTACTS IN ROWS B,D,F,H,L,N,Q AND S
ARE DUAL BEAM CONTACTS,
TYPICALLY USED AS SIGNAL PINS.⑥ SPECIFIED POSITIONAL TOLERANCE DEFINES PAD TO PAD
LOCATION WITHIN LAND PATTERN. POSITIONAL TOLERANCE
OF LAND PATTERN TO FUDICIAL MARKS OR PCB DATUMS
SHALL BE DEFINED BY CUSTOMER. FOR RECOMMENDED
PRODUCT APPLICATION AND PCB DESIGN DETAILS, SEE
DOC. NO. GS-20-016.⑦ FOR PROPER APPLICATION FOLLOW FCI APPLICATION
SPECIFICATION GS-20-033 LEADFREE SOLDER BALLS WILL NOT
SOLDER PROPERLY IN A LEADED SOLDER PROCESS DUE TO A
HIGHER REFLOW TEMPERATURE, LEAD FREE PRODUCT IS
THEREFORE NOT BACKWARDS COMPATIBLE WITH LEADED
OR SOME SOLDERING APPLICATIONS, REFERENCE FCI
APPLICATION SPECIFICATION.⑧ THIS PRODUCT MEETS THE EUROPEAN UNION DIRECTIVES
AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN
GS-22-008 PRODUCT MEETING THIS DIRECTIVE IS
IDENTIFIED IN THE LOT CODE NUMBER MARKED
ON EACH PART BY HAVING AN "X" IN THE SEVENTH
CHARACTOR POSITION.

spec ref -				dr	Bill Lin	2010/02/02	projection 		mm	size	A4	scale	1:1
tolerance std ASME Y14.5 -	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Nickor Zuo	2011/06/13			ecn no	ELX-DG-003943-1			
				chr	Alex Cao	2011/06/24			rel level Released				
				appr	Pei-Ming Zheng	2011/06/27							product family
surface ✓ -	linear	0.X	±0.30		title GIG-Array 13mm PLUG ASSY. 200 SIG. POS.			dwg no	10055142		rev G		
		0.XX	±0.10										
		0.XXX	±0.05										
		angular	0°	±2°	www.fci.com	cat. no.		Product - Customer Drw			sheet 5 of 5		

PrintE File - REV C - 2009-06-09

PDS: Rev :G

STATUS:Released

Printed: Jun 27, 2011