

CONNECTOR: 859S005-10SRRM4

24 AWG (7X32) HOOKUP WIRE, UL 1007
(COLORS AS STATED IN SCHEMATIC BELOW)

**SEE PAGE 2 FOR DETAILS

WIRING SCHEMATIC

1	2
PIN	PIN
1 = BROWN	1 = RED
2 = WHITE	2 = GREEN
3 = BLUE	3 = BLACK
4 = BLACK	4 = WHITE
5 = GREY	5 = GREY

MPM12A05IYYDR0Y

INCHES

01 = WIRING SCHEMATIC 1
02 = WIRING SCHEMATIC 2
LENGTH
EX: 06 = 6 INCHES
12 = 12 INCHES

NOTE: PACKAGED 10 PER BAG

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE
THE PROPERTY OF NorComp AND SHALL NOT
BE REPRODUCED, COPIED OR USED AS THE
BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS WITHOUT WRITTEN PERMISSION.



DRAWN:	G. BROWN
DATE:	01/23/2019

UNITS IN INCHES [MM] DO NOT SCALE FROM DRAWING

NorComp

SCALE:	NTS	SHEET	OF	
		1	2	REV 1
DWG NO.	MPM12A05IYYDR0Y			

DESCRIPTION: M12 5 POSITION STAINLESS STEEL MALE PIGTAIL



NOTE:

MATERIAL
HOUSING:
CONTACT:
NUT:
SHELL:
O-RING:

PBT UL94V-0, BLACK
BRASS
STAINLESS STEEL 316
STAINLESS STEEL 316
EPDM, BLACK



FINISH
CONTACT:
UNDER PLATE:
ELECTRICAL
RATED CURRENT:
RATED VOLTAGE:
INSULATION RESISTANCE:
CONTACT RESISTANCE:
WATER PROOF:
ENVIRONMENT
OPERATION TEMPERATURE:

GOLD PLATED 10 μ Min.
NICKEL

4A
60V
100M Ω MIN
10m Ω MAX
IP67/68

-40°C ~ +85°C

RECOMMENDED PANEL CUT-OUT



RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE
THE PROPERTY OF NorComp AND SHALL NOT
BE REPRODUCED, COPIED OR USED AS THE
BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
G. BROWN
DATE:
01/23/2019

UNITS IN INCHES [MM] DO NOT SCALE FROM DRAWING

NorComp

SCALE: NTS	SHEET 2	OF 2	REV 1
DWG NO. MPM12A05IYYDR0Y			