FEATURES:

- 12 OR 24 VOLTS DC OPERATION
- 96 WATT HANDLING CAPABILITY AT 12V
- 196 WATT HANDLING CAPABILITY AT 24V
- WIDE SENSOR FIELD OF VIEW

60.0mm (2.40")	Hole for #6 Screw [4plcs]	
AMBIENT LIGHT SWITCH		
O OFF	64.0mm (2.52")	77.0mm (3.03") 89.0mm (3.50")
DC12-24V 8A IN OUT V- V+ V+ V-		
0000		
39.0mm (1.54")		

45.0mm

20.4MM (.80")

- -GND

POWER OUTPUT

-GND-

+ V——POWER INPUT

	REV.	DESCRIPTION/ECO NO.	DATE
		RELEASED	9/30/13
	Α	CHANGE DIMENSION 89.0 TO 64.0	10/24/13
ſ			
ſ			
Ì			



RATINGS

CHARACTERISTICS	UNIT	MINIMUM	MAXIMUM		
Input Voltage	Volts DC	12	24		
Load Current	Amps	8	8		
Operating Temperature	Degrees C	-20	60		
Trigger Range ON	Lux	85			
Trigger Range OFF	Lux		215		

JKL PART NO.: ZCTR-04

METRIC DIMENSIONS ARE IN mm (INCHES)

METRIC	DIMENSIONS ARE IN mm (INCHES)		KI	COMPONE	ENITE CODD	OD A TION
$ +(\oplus)-+-+$	TOLERANCE UNLES		JAL COMPONENTS CORPORAT		UKATION	
THIRD ANGLE PROJECTION	1 PL +/- REF. 2 PL +/- REF. ANGLE +/- REF.	TITLE	PHOTO SENSOR SWITCH			
DRAWN BY	APPV'D BY DATE	SIZE	FSCM NO.	DRAWING	70TD 04	
L. WENGSTROM	L.R. 9/30/	13 A	55335	NO.	ZCTR-04	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NOT	TO SCALE	RELEASED 9/30/13	DATE 10/24/13	NO. A 1 OF 1