# **XAPG19400**



#### Main

Range of product	Harmony XAP
Product or component type	Die-cast empty control station
Device short name	XAPG
Product destination	For Ø 22 mm control and signalling units
Number of cut-out	Undrilled
Colour of base of enclosure	Grey RAL 7032
Colour of cover	Grey RAL 7032
Material	Zinc alloy
Cable entry	1 hole with blanking plug for cable gland with <= 0.55 in (14 mm) 1 hole without blanking plug for cable gland with <= 0.55 in (14 mm)
Product mounting	Flush mounting
IP degree of protection	IP65 conforming to IEC 60529 IP657 conforming to NF C 20-010

# Complementary

|--|

### **Environment**

protective treatment	TC	
ambient air temperature for storage	-40158 °F (-4070 °C)	tain an
ambient air temperature for operation	-13158 °F (-2570 °C)	000 %
electrical shock protection class	Class I conforming to IEC 60536 Class I conforming to NF C 20-030	- Inpoud

# Offer Sustainability

WARNING: This product can expose you to chemicals including:		
Nickel compounds, which is known to the State of California to cause cancer, and		
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive harm. harm.		
For more information go to www.p65warnings.ca.gov		

### Contractual warranty

Warranty period	18 months