

f	0	0	0	0	0	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K		
e	F	F	0	F	0	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
d	0	0	0	F	0	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
c	F	F	0	0	0	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
b	0	0	0	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
a	F	F	0	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
z	0	0	0	0	0	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K		
P O S	0 1					0 5					1 0					1 5					2 0					2 5

Technical drawing of a 1200mm x 1200mm floor slab with a 150mm drop at the perimeter. The drawing includes a plan view and a section view.

Plan View Dimensions:

- Overall width: 15.40 ± 0.50
- Overall depth: 11.70 ± 0.10
- Drop height: 3.00 ± 0.10
- Reinforcement spacing: $2.00 \pm 0.05 (24x)$

Section View Dimensions:

- Overall height: 12.00
- Drop height: $2.00 \pm 0.05 (6x)$
- Drop width: 50.0 MAX
- Reinforcement spacing: $2.00 \pm 0.05 (24x)$

Notes:

- NOTE 3: Reinforcement bars are 12mm diameter.
- NOTE 5: Reinforcement bars are 12mm diameter.
- NOTE 6: Reinforcement bars are 12mm diameter.

SEATING PLANE FOR CONNECTOR

9.70 16.00

F

11.20 16.00

K

A diagram of a rectangular field with a width of 48.00 and a height of 12.00. The field is filled with a grid of 400 small circles, arranged in 20 rows and 20 columns. The circles are evenly spaced, representing the locations of the 400 sensors.

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

[illegible]