

PKGS-25SXAP1-R












Appearance & Shape







Applications

Other Usage

For consumer use



Packaging Information

Packaging	Specifications	Minimum Order Quantity
R	180mm Embossed Tape	3000

1 of 3





PKGS-25SXAP1-R




Operating Temperature Range	-40℃ to 85℃	
Primary Axis Inclined Angle	25°	
Sensitivity(typ.)	0.35pC/G	
Capacitance(typ.)	740pF	
Insulation Resistance(min.)	100ΜΩ	
Non-linearity(typ.)	1%	
Shock Resistance	3000G (0.3ms duration)	
Sensitivity Type	Electric charge sensitivity type	
Resonance Frequency	27kHz	
Storage Temperature Range	-40°C to 85°C	






PKGS-25SXAP1-R







Freq. Characteristics

Primary axis inclined angle

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





URL: http://www.murata.com/