







THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2012/10/22	Ruru	HC20-02RMFS-SS8001 To HC20-02PMFS-SN8001
B	LEN14A0101	2014/09/13	Feng_Li	Change Logo Direction
C	LE31650213	2016/05/03	Vicky	Update Note


ALTW
CONFIDENTIAL
2016-05-03
R&D DEPT.



ALTW
DCC. DEPT.
CONFIDENTIAL
2016.05.13
ISSUED



Recommend Panel Cut-Out



- △ Note:
- * $\varnothing$ Important Dimension.
 - * Waterproof Rate: IP68.
IP68: 1M depth of water in 24 Hrs.
(防水等級: IP68)
IP68: 水深一米測試 24 小時
 - * Shell: Zinc Alloy ,Electrodeposition Coating,Black.
 - * Insulation: Nylon ,Black.
 - * Female Pin: Copper Alloy ,Gold Plated.
 - * Gasket: Silicone ,Gray.
 - * Recommended Panel Thickness 5.0mm(Max).

UNIT:mm		TITLE PANEL NUT 2PIN M CONN F PIN		Amphenol LTW		ITEM NO HC20-02PMFS-SN8001	DRAWN BY Vicky	DATE 2016-05-03
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 1:1	SIZE A4	SHEET 1 OF 1		DWG NO HC20-02PMFS-SN8001	CHECKED BY Rita	DATE 2016-05-03
REV. C		WC-REV. A.3	$\varnothing$ Inspection item		CUSTOMER ALTW		APPROVED BY Lisa	DATE 2016-05-03

安費諾亮泰企業股份有限公司