## **ZCKD109**





## .....

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Plunger head
Product compatibility	XCKL XCKM
Associated body	ZCKL1 ZCKL1H7 ZCKL5 ZCKL5H7 ZCKL6 ZCKL6H7 ZCKL7 ZCKL7 ZCKL7 ZCKL7 ZCKL8 ZCKL8H7 ZCKL031 ZCKL031 ZCKL035 ZCKL035 ZCKL037H7 ZCKL037 ZCKL039 ZCKL039H7 ZCKM1429 ZCKM1H29 ZCKM5H29 ZCKM5H29 ZCKM6H29 ZCKM6H29 ZCKM6H7 ZCKM6 ZCKM6H29 ZCKM6H7 ZCKM6 ZCKM6H29 ZCKM6H7 ZCKM7 ZCKM7 ZCKM8 ZCKM8 ZCKM8 ZCKM8H29 ZCKM8H29 ZCKM8H29 ZCKM8H29 ZCKM8H29 ZCKM8H29 ZCKM8 ZCKM8H29 ZCKM8H29 ZCKM8 ZCKM8 ZCKM8 ZCKM8 ZCKM8 ZCKM8 ZCKM8 ZCKM8 ZCKM031 H29 ZCKM031 ZCKM035 ZCKM035 ZCKM037 ZCKM039 ZCKM03
Movement of operating head	Linear
Type of operator	Enterna End plunger spring return metal (with protective boot)

ZCK	D109	



Switch actuation

On end



Positive opening	With	
Head material	Plastic	
Environment		

LINIONNEIL	
ambient air temperature for operation	-13158 °F (-2570 °C)
ambient air temperature for storage	-40158 °F (-4070 °C)
environmental characteristic	Standard environment

## **Offer Sustainability**

Green Premium product	Green Premium product
Compliant - since 1012 - Schneider Electric declaration of conformity	Compliant - since 1012 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

## Contractual warranty

Warranty period

18 months

