



2104



2104-X-01-XX-00-00-07-0
Swage mount in .036 hole

- X -	Board Thickness	Length V
1	.031	.055
2	.062	.086
3	.094	.117
4	.125	.148


2112



2112-X-01-XX-00-00-07-0
Swage mount in .043 hole

- X -	Board Thickness	Length V
5	.016	.037
1	.031	.053
2	.062	.084
3	.094	.115
4	.125	.147


2105



2105-X-01-XX-00-00-07-0
Swage mount in .052 hole

- X -	Board Thickness	Length V
1	.031	.055
2	.062	.086
3	.094	.117
4	.125	.149


2103




2103-X-01-XX-00-00-07-0
Swage mount in .052 hole

- X -	Board Thickness	Length V
1	.031	.055
2	.062	.086
3	.094	.117
4	.125	.149

2106/2107



2106-X-01-XX-00-00-07-0
Swage mount in .052 hole



2107-X-01-XX-00-00-07-0
Swage mount in .052 hole

- X -	Board Thickness	Length V
1	.031	.051
2	.062	.082
3	.094	.113
4	.125	.145

SPECIFICATIONS

PIN MATERIAL:
Brass Alloy 360, 1/2 Hard
Swage pins are annealed

DIMENSION IN INCHES
TOLERANCES ON:
LENGTHS: $\pm .005$
DIAMETERS: $\pm .002$
ANGLES: $\pm 2^\circ$

ORDER CODE: XXXX - X - 01 - XX - 00 - 00 - 07 - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01 200 μ " TIN/LEAD OVER NICKEL
- ◇ 80 200 μ " TIN OVER NICKEL (RoHS)
- ◇ 44 300 μ " SILVER OVER COPPER (RoHS)
- ◇ 50 300 μ " ELECTRO-SOLDER (RoHS) (60/40 SnPb)

