





Heyco® Nylon PCB Supports - Imperial Spacing




FLANGED TWO PRONG SNAP FIT /
FLANGED TWO PRONG SNAP LOCK

HMSPS




FLAT TOP REST MOUNT /
ARROWHEAD LOCK

HMPS



FLAT TOP REST MOUNT /
TEARDROP SNAP LOCK

HPS-TD



TEARDROP SNAP LOCK /
TEARDROP SNAP LOCK

HSP-MDL-3

		Maximum Thickness		Mounting Hole Diameter		Maximum Thickness		Mounting Hole Diameter		Maximum Thickness		Mounting Hole Diameter		Maximum Thickness		Mounting Hole Diameter	
		in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.
PCB		.062	1,6	.157	4,0	flat top rest mount				flat top rest mount				.062	1,6	.098	2,5
Chassis		.062	1,6	.157	4,0	.078	2,0	.125	3,2	.062	1,6	.098	2,5	.039	1,0	.078	2,0
A		PART NO.		DESCRIPTION		PART NO.		DESCRIPTION		PART NO.		DESCRIPTION		PART NO.		DESCRIPTION	
in.	mm.	Natural				Natural				Natural				Natural			
.063	1,6									10341		HPS-TD-01		10352		HSP-MDL-3-01	
.125	3,2					10331		HMPS-02		10342		HPS-TD-02		10353		HSP-MDL-3-02	
.187	4,8	10320		HMSPS-03		10332		HMPS-03		10343		HPS-TD-03		10354		HSP-MDL-3-03	
.250	6,4	10321		HMSPS-04		10333		HMPS-04		10344		HPS-TD-04		10355		HSP-MDL-3-04	
.312	7,9	10322		HMSPS-05		10334		HMPS-05		10345		HPS-TD-05		10356		HSP-MDL-3-05	
.375	9,5	10323		HMSPS-06		10335		HMPS-06		10346		HPS-TD-06		10357		HSP-MDL-3-06	
.437	11,1	10324		HMSPS-07		10336		HMPS-07		10347		HPS-TD-07					
.500	12,7	10325		HMSPS-08		10337		HMPS-08		10348		HPS-TD-08					
.562	14,3					10338		HMPS-09		10349		HPS-TD-09					
.625	15,9	10326		HMSPS-10		10339		HMPS-10		10350		HPS-TD-10					
.689	17,5	10327		HMSPS-11													
.750	19,1	10328		HMSPS-12													
.875	22,2	10329		HMSPS-14													

Standard color natural. For special order parts in UL 94V-0 natural material, add the suffix “F” to Part No.

Material: Nylon 6/6
Flammability Rating: 94V-2
Temperature Range: .4°F (-18°C) to 185°F (85°C)

*Quick
Specs*