

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA

Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

TIP47 THRU TIP50

NPN SILICON HIGH VOLTAGE
POWER TRANSISTOR

JEDEC TO-220AB CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR TIP47 Series types are Silicon NPN Triple Diffused Mesa Power Transistors designed for high voltage applications such as power supplies and other switching applications.

MAXIMUM RATINGS (T_C=25°C unless otherwise noted)

	SYMBOL	TIP47	TIP48	TIP49	TIP50	UNIT
Collector-Base Voltage	V _{CB0}	350	400	450	500	V
Collector-Emitter Voltage	V _{CE0}	250	300	350	400	V
Emitter-Base Voltage	V _{EB0}		5.0			V
Collector Current	I _C		1.0			A
Collector Current-Peak	I _{CM}		2.0			A
Base Current	I _B		0.6			A
Power Dissipation	P _D		40			W
Unclamped Inducting Load	E		20			mJ
Operating and Storage Temperature	T _J , T _{stg}		-65 TO +150			°C
Thermal Resistance	θ _{JC}		3.13			°C/W

ELECTRICAL CHARACTERISTICS (T_C=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
I _{CES}	V _{CE} =Rated V _{CB0}		1.0	mA
I _{CE0}	V _{CE} =150V (TIP47)		1.0	mA
I _{CE0}	V _{CE} =200V (TIP48)		1.0	mA
I _{CE0}	V _{CE} =250V (TIP49)		1.0	mA
I _{CE0}	V _{CE} =300V (TIP50)		1.0	mA
I _{EB0}	V _{BE} =5.0V		1.0	mA
BV _{CE0}	I _C =30mA (TIP47)	250		V
BV _{CE0}	I _C =30mA (TIP48)	300		V
BV _{CE0}	I _C =30mA (TIP49)	350		V
BV _{CE0}	I _C =30mA (TIP50)	400		V
h _{FE}	V _{CE} =10V, I _C =0.3A	30	150	
h _{FE}	V _{CE} =10V, I _C =1.0A	10	-	
h _{fe}	V _{CE} =10V, I _C =0.2A, f=1.0kHz	25		
V _{CE(SAT)}	I _C =1.0A, I _B =0.2A		1.0	V
V _{BE(ON)}	V _{CE} =10V, I _C =1.0A		1.5	V
f _T	V _{CE} =10V, I _C =0.2A, f=2.0MHz	10		MHz

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms



<http://www.centrasemi.com>

Product End of Life Notification

PDN ID:	PDN01040
Notification Date:	8/11/16
Last Buy Date:	2/11/17
Last Shipment Date	8/11/17

Summary: The TIP47 series of NPN, high voltage, power transistors, with the exception of TIP50, is discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement
TIP47	TIP50
TIP47 SL	TIP50
TIP48	TIP50
TIP49	TIP50
TIP49 SL	TIP50
TIP49 TR	TIP50

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centrasemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.